



ProLite X2377HDS - a 23" LED backlit LCD Screen featuring IPS Panel technology which is considered to be the best all around panel type. This IPS panel offers accurate and consistent colour reproduction with wide viewing angles (178°/178°) and great response time (5 ms black-to-black). The ProLite X2377HDS is full HD, has a 5 000,000:1 Advanced Contrast Ratio and 250 cd/m² brightness offering the user clear and vivid images. An array of inputs including HDMI, DVI and VGA connections ensure compatibility across a range of devices including games consoles and work stations. The Prolite X2377HDS has two integrated stereo speakers and is VESA mount compatible. It will provide both excellent performance for photographic, design and web-design and is also an excellent choice for Universities, Corporate and Financial Markets, as well as the rapidly expanding demand for Multi Monitor applications.

01 DISPLAY CHARACTERISTICS

Diagonal	23", 58.4cm
Panel	IPS
Native resolution	1920 x 1080 (Full HD 1080p, 2.1 megapixel)
Aspect ratio	16:9
Panel brightness	250 cd/m ²
Static contrast	1000:1
Advanced contrast	5M:1
Response time (GTG)	5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn
Horizontal Sync	30 - 80kHz
Viewable area W x H	509.2 x 286.4mm, 20 x 11.3"
Pixel pitch	0.265mm

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	VGA x1 DVI x1 HDMI x1
USB HUB	x0

03 FEATURES

OSD languages	EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Menu/ Select, +/- Volume, -/ ECO, Auto/ Exit
User controls	picture (brightness, contrast, H. position, V. position, phase, clock, colour temp., auto adjust), OSD (H. position, V. position, OSD time out), display (display mode, i-style Colour, Adv. Contrast, ECO, sharpness, Over Drive), audio (volume, mute, audio input), miscellaneous (language, input select, opening logo, reset), information
Speakers	2 x 1.5W

04 MECHANICAL

Tilt angle	15° up; 5° down
VESA mounting	100 x 100mm

05 ACCESSORIES INCLUDED

Cables	power
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	32W typical, 0,5W stand by, 0,5W off mode

07 SUSTAINABILITY

Regulations	TCO Certified, CE, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	546 x 394.5 x 164mm
Weight (without box)	3.4kg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED