



27" IPS panel technology, ultra slim monitor featuring 4K resolution and Dynamic Power Saving (DPS)

The ProLite XU2792UHSU with its stylish front design and 4K resolution effortlessly accommodates four times more information than a Full HD display. Equipped with IPS panel for precise color reproduction and wide viewing angles, alongside high contrast and brightness values, it ensures impeccable performance for both photographic and web design tasks. A With the Dynamic Power Saving (DPS) feature, simply toggle a switch to enjoy intelligent brightness adjustment for optimal energy efficiency without compromising on brilliance. Redefine your creative workflow with the ProLite XU2792UHSU.

Available also with height adjustable stand : [ProLite XUB2792QSU-B6 \(2560x1440\)](#) a n d [ProLite XUB2792HSU-B6 \(1920x1080\)](#)



Dynamic Power Saving (DPS)

Dynamic Power Saving (DPS) intelligently detects the current image and adjusts brightness dynamically to save power. The default setting is « On » which may slightly dim the screen. Simply switch to « Off » for optimal brightness.



IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

01 DISPLAY CHARACTERISTICS

Design	3-side borderless
Diagonal	27", 68.5cm
Panel	IPS LED, matte finish
Native resolution	3840 x 2160 @60Hz (DisplayPort, 8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	1300:1
Advanced contrast	80M:1
Response time (GTG)	4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 8bit (sRGB: 100%, NTSC 72%)
Horizontal Sync	30 - 140kHz
Viewable area W x H	596.7 x 335.7mm, 23.5 x 13.2"
Pixel pitch	0.155mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.2.0) DisplayPort x1 (v.1.2)
USB HUB	x3 ((v.3.2 Gen 1 (5Gbit; 4.5W))
USB-C	x1 (Power delivery 15W)
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Joystick: Center (Power/Menu), Up (Input Select), Down, Right (Volume/Mute), Left (Submenu)
User controls	picture adjust (brightness, contrast, ECO, ACR, OD, X-Res technology, DPS), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI, display information), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, LED, USB BC), input select (source) audio settings (volume, mute)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	tilt
Tilt angle	20° up; 4° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables

power, USB, HDMI, DP

Other

quick start guide, safety guide

06 POWER MANAGEMENT**Power supply unit**

internal

Power supply

AC 100 - 240V, 50/60Hz

Power usage

34W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY**Regulations**

TCO Certified, CE, TÜV-GS, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369)

F

REACH SVHC

above 0.1%: Lead

08 DIMENSIONS / WEIGHT**Product dimensions W x H x D**

614.5 x 439.5 x 190mm

Box dimensions W x H x D

688 x 473 x 124mm

Weight (without box)

4.7kg

Weight (with box)

7.1kg

EAN code

4948570123797



