



43" 4K UHD professional digital signage display with advanced control and connectivity options


Elevate your visual communication with the LH4360UHS-B1AG and unlock the new possibilities for your business. This 500cd/m² high brightness display is a powerful business tool that takes your marketing and communication efforts to the next level. With its Android 11 OS, iiSignage² content management software, Signal FailOver and [EShare](#) features, this display offers a straightforward user experience, making content creation, management, and sharing a breeze.

This ELED VA display consumes significantly less power compared to DLED IPS while maintaining the same level of brightness. Its versatile orientation, sleek design, and 24/7 reliability ensure it seamlessly integrates into any business environment. Whether it's used in retail, corporate, hospitality, or educational settings, the LH4360UHS-B1AG will undoubtedly captivate your audience and leave a lasting impression.



Android OS

Zahvaljujući Android operativnom sistemu, ekran možete lako prilagoditi svojim potrebama instaliranjem aplikacija direktno na njega.



iiSignage²

iiSignage² je naša platforma za upravljanje sadržajem digitalnog oglašavanja koja lako prikazuje i kontroliše vaš sadržaj i upravlja vašim ekranima. Sistem za upravljanje sadržajem (CMS) vam daje potpunu kontrolu nad vašim porukama i oglašavanjem bezbedno i na daljinu.

01 KARAKTERISTIKE EKRANA

| | |
|------------------------------------|---|
| Dizajn | Tanki okvir |
| Dijagonala | 42.5", 108cm |
| Panel | VA, AG presvučeno staklo, mat završna obrada, hard coating (3H), haze 25% |
| Osnovna rezolucija | 3840 x 2160 @60Hz (8.3 MegaPixels 4K UHD) |
| Osnovna rezolucija | 60Hz |
| Format ekrana | 16:9 |
| Osvetljenje | 500 cd/m ² |
| Statički kontrast | 5000:1 |
| Vreme odziva (GTG) | 8,5ms |
| Zona gledanja | horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89° |
| Podržane boje | 1.07G (8 Bits+FRC) (NTSC 87%) |
| Horizontalna sinhronizacija | 28 - 160KHz |
| Vidljiva površina Š x V | 941.2 x 529.4mm, 37.1 x 20.8" |
| Širina okvira (stranice, vrh, dno) | 9mm, 9mm, 9mm |
| Razmak piksela | 0.245mm |
| Boja okvra | crna, mat |

02 KONEKTORI / KONTROLE

| | |
|-------------------------|--|
| Ulaz digitalnog signala | HDMI x3 (v.2.0, max. 3840x2160 @60Hz) |
| Audio ulaz | Mini konektor x1 (3.5mm) |
| Kontrolni ulaz | RS-232c x1 (2.5mm sub-mini jack) RJ45 (LAN) x1 IR x1 (3.5mm stereo mini) |
| Audio izlaz | Mini konektor x1 Zvučnici 2 x 10W |
| HDCP | v.1.4 & 2.2 |
| USB portovi | x2 (v.2.0) |

03 KARAKTERISTIKE

| | |
|-----------------------------------|--|
| Integrirani softver | Android 11 OS, iiSignage ² , FailOver, EShare |
| WiFi | da (Ugradni, 802.11ac) |
| Hardver | CPU: A53*4, GPU: G52 MP2, RAM: 2GB, ROM: 16GB |
| Dodatno | Wall mounting kit included (VESA 400x300mm) |
| Maksimalno neprekidno radno vreme | 24/7 |
| Protiv zadržavanja slike | da |
| Reprodukcija medija | da |
| Kućiste (okvir) | plastika |

04 OPŠTE

| | |
|-------------------|--|
| OSD jezici | EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL |
| Kontrolni tasteri | Power button, Power Indicator, Remote Sensor |

Korisničke kontrole

picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temperature, colour control, over scan, picture reset), screen (zoom mode, custom zoom, screen reset), Audio (balance, treble, bass, volume, audio out, maximum volume, minimum volume, mute, audio out sync, speaker setting, audio reset), configuration 1 (switch on state, panel saving, RS232-routing, boot on source, WOL, configuration 1 reset, factory reset), Configuration 2 (OSD timeout, OSD H-Position, OSD V-position, system rotation, information OSD, logo and animation logo setting, animation setting, monitor ID, monitor information, HDMI version, configuration 2 reset), advanced option (IR control, off timer, schedule, HDMI with one wire, HDMI with one wire power off, FailOver, language, OSD transparency, power saving, advanced option reset), Android settings (network & internet, apps & notifications, display, signage display, security, language & input, date & time, about device)

Plug&Play

DDC2B

05 MEHANIČKI

Orijentacija

pejzaž, portret

Dizajniran bez ventilatora

da

VESA montiranje

400 x 300mm

Opseg radne temperature

0°C - 40°C

Temperatura skladištenja

- 20°C - 60°C

MTBF - Prosečno vreme izmedju kvarova

50.000 sati (izuzimajući pozadinsko osvetljenje)

06 UKLJUČENI DODACI

Kablovi

Strujni kabl, HDMI, RS-232c

Upustva

kratko uputstvo, bezbednosni vodič

Ostalo

Wall mount bracket, Wall mount guide, Screws, Screw anchors, Stickers for screw holes

Daljinski upravljač

da (baterije uključene)

07 UPRAVLJANJE NAPAJANJEM

Napajanje

interna

Potrošnja energije

% 1W tipično, 0.5W stand by

08 ODRŽIVOST

Propisi

CB, CE, TÜV-Bauart, EAC, RoHS podrška, ErP, WEEE, REACH, UKCA

Klasa energetske efikasnosti (Regulation (EU) 2017/1369)

G

09 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D

967.4 x 555.9 x 40mm

Dimenzije kutije Š x V x D

1075 x 652 x 144mm

Težina (bez kutije)


9.1kg

Težina (sa kutijom)

12.7kg

EAN kod

4948570122295



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED