

UC-CAM10PRO-1 preliminary

	UNIFIED COMMUNICATIONS	
— BİLGİLER		
— DIEGIEEN		

120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.

2D & 3D Digital Noise Reduction

Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.

Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.

ÖZELLIKLER

01 KAMERA

Piksel	8,46M

Supported 2160p/30fps, 1440p/30fps, 1080p/30fps resolutions

Çapraz görüş alanı 120°

(dFoV)

Odak modu fixed

Odak mesafesi 8m

Diyafram 2.5

Zoom 5x digital zoom

AutoFraming Evet

02 SES

Mikrofon dizisi sayısı 2

Ses alma mesafesi 4n

Ses alma açısı 180°

03 BAĞLANTI

Host USB v.3.0

04 MIKROFON

Number of x2 microphone arrays

Voice pickup range 4m (radius)

05 CONNECTIVITY & BUTTON OPERATIONS

USB Type C x1

06 MEKANİK

Eğim açısı ≤14°

Döndürme 360°

Gizlilik deklanşörü yes

07 ÖLÇÜLER / AĞIRLIK

Ürün boyutları G x Y x 80 x 75 x 53mm

D

Kutu boyutları G x Y x 162 x 124 x 90mm

Е

Ağırlık (kutu hariç) 0.21kg

Ağırlık (kutu ile birlikte) 0.5kg

EAN kodu 4948570033140



İlgili ürünler UC CAM120ULB-1, UC CAM180UM-1, UC CAM80UM-1, UC SPK01M

UC-CAM10PRO-1(22)-black.jpg	UC-CAM10PRO-1(10).jpg
UC-CAM10PRO-1(10)-black.jpg	UC-CAM10PRO-1(23).jpg

– GALERİ

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED