

## Wireless presentation USB-C dongle

The wireless presentation dongle allows to share content (e.g. videos, applications) from your computer to an iiyama (i)LFD with the pre-installed EShare app. It is compatible with computers equipped with USB-C (DP-Alt mode) and supports smooth video streaming up to 4K.

To use the dongle you need to pair it with the Android receiver. The included USB Type-C to A adapter can be used if the Android receiver doesn't have a Type-C connection.

### 01 DEVICE

<b>Supported platforms</b>	Windows, MAC, Chrome, Any OS which supports full feature Type-C (DP-Alt supported)
<b>DisplayPort Out</b>	x1 (1.2, complies with HDCP)
<b>Audio</b>	stereo, radio quality 16bits 48kHz
<b>Frame rate</b>	Up to 60 fps depending on environment (FHD) and 30fps for 4K
<b>Output resolution</b>	720x480, 720x576, 1280x720, 1920x1080(1080P), 3840x2160@30Hz
<b>Features</b>	Included: USB type-C to A adapter (to pair devices)
<b>Input resolution</b>	Video: 480p, 576p, 720p, 1080p
<b>Wireless</b>	IEEE 802.11n, 5GHz
<b>Data rate wireless</b>	up to 300Mbps
<b>Authentication protocol</b>	WPA2(WPA2-PSK (Pre-Shared key) / WPA2- Enterprise)
<b>Security (encryption)</b>	WPA2
<b>Reach</b>	20 m max.

### 02 TECHNICAL SPECIFICATION

<b>Colour</b>	silver, black
<b>Software</b>	Connects with EShare app version 7.3 and higher.

### 03 POWER MANAGEMENT

<b>Power supply unit</b>	external
--------------------------	----------

<b>Power usage</b>	4.5W typical
--------------------	--------------

## 04 SUSTAINABILITY

<b>Regulations</b>	CE, RoHS support, WEEE, REACH
--------------------	-------------------------------

## 05 DIMENSIONS / WEIGHT

<b>Product dimensions W x H x D</b>	57 x 175 x 17mm
-------------------------------------	-----------------

<b>Box dimensions W x H x D</b>	100 x 123 x 33mm
---------------------------------	------------------

<b>Weight (without box)</b>	0.81kg
-----------------------------	--------

<b>Weight (with box)</b>	0.217kg
--------------------------	---------

<b>EAN code</b>	4948570032891
-----------------	---------------

## 06 ENVIRONMENTAL CONDITIONS

<b>Operation temperature range</b>	0°C - 40°C
------------------------------------	------------

<b>Operation humidity</b>	10% - 80%
---------------------------	-----------

<b>Storage temperature range</b>	- 10°C - 60°C
----------------------------------	---------------

<b>Storage humidity</b>	5% - 90%
-------------------------	----------

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED