



## 21.5" IPS Full HD monitor with USB hub and 100Hz refresh rate

Stylish edge-to-edge design makes the ProLite XU2293HSU perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, headphone socket, 2 port USB hub, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue for user comfort, this 21.5" display is a great choice for home and office applications.

Available also with height adjustable stand : [ProLite XUB2293HS-B6](#)

### IPS Technology

IPS displays are best known for wide viewing angles and natural, highly accurate colours. They are especially suited for colour-critical applications.

### Full HD

With true 1920 x 1080p resolution your monitor is ready to display high definition images. This means you can accommodate more information on your screen; e.g. 60% more in comparison to a 1280 x 1024 monitor.

## 01 DISPLAY CHARACTERISTICS

|                      |   |
|----------------------|---|
| Design               | 3-side borderless   |
| Diagonal             | 21.5", 54.5cm   |
| Panel                | IPS panel technology LED, matte finish                                |
| Native resolution    | 1920 x 1080 @100Hz (2.1 megapixel Full HD)                            |
| Aspect ratio         | 16:9  |
| Panel brightness     | 250 cd/m <sup>2</sup>   |
| Static contrast      | 1000:1  |
| Advanced contrast    | 80M:1   |
| Response time (MPRT) | 1ms   |
| Viewing zone         | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support       | 16.7mIn (sRGB: 96%; NTSC: 72%)  |
| Horizontal Sync      | 30 - 110kHz   |
| Viewable area W x H  | 478.7 x 260.3mm, 18.8 x 10.3"   |
| Pixel pitch          | 0.249mm   |
| Colour               | matte, black  |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |                           |
|---------------------|---------------------------|
| Signal input        | HDMI x1<br>DisplayPort x1 |
| USB HUB             | x2 (2.0 (DC5V, 500mA))    |
| HDCP                | yes                       |
| Headphone connector | yes                       |

## 03 FEATURES

|                       |   |
|-----------------------|---|
| Blue light reducer    | yes   |
| Flicker free          | yes   |
| Adaptive Sync support | yes   |
| Extra                 | i-style Colour  |
| OSD languages         | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL  |
| Control buttons       | Power, Menu, Up / Right / Volume, Down / Left / i-Style Colour, Input / Exit  |
| User controls         | picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync ), colour settings (i-Style colour, blue light reducer, colour temp., user preset), OSD (OSD H. position, OSD V. position, OSD time), language, recall, miscellaneous (soft and sharp, video mode adjust, opening logo, RGB range, LED, display information), input select (source), audio settings (volume, mute) |
| Speakers              | 2 x 2W  |
| Convenience           | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX   |

## 04 MECHANICAL

|                              |                 |
|------------------------------|-----------------|
| Display position adjustments | tilt            |
| Tilt angle                   | 22° up; 4° down |
| VESA mounting                | 100 x 100mm     |
| Cable management system      | yes             |

## 05 ACCESSORIES INCLUDED

|               |                                 |
|---------------|---------------------------------|
| <b>Cables</b> | power, USB, HDMI                |
| <b>Other</b>  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

|                          |   |
|--------------------------|---|
| <b>Power supply unit</b> | internal                                  |
| <b>Power supply</b>      | AC 100 - 240V, 50/60Hz                    |
| <b>Power usage</b>       | 17W typical, 0.5W stand by, 0.3W off mode |

## 07 SUSTAINABILITY

|  |   |
|--|---|
| <b>Regulations</b>   | TCO Certified, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| <b>Energy efficiency class (Regulation (EU) 2017/1369)</b> | E   |
| <b>REACH SVHC</b>  | above 0.1%: Lead  |

## 08 DIMENSIONS / WEIGHT

|                                     |                   |
|-------------------------------------|-------------------|
| <b>Product dimensions W x H x D</b> | 492 x 359 x 178mm |
| <b>Box dimensions W x H x D</b>     | 564 x 380 x 122mm |
| <b>Weight (without box)</b>         | 2.6kg             |
| <b>Weight (with box)</b>            | 3.6kg             |
| <b>EAN code</b>                     | 4948570123018     |

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED