



## 24" IPS monitor sa ugrađenom WindowsHello kamerom i mikrofonom

XUB2490HSUH je prvoklasni desktop monitor od 24" dizajniran za profesionalnu i ličnu upotrebu. IPS matrica obezbeđuje preciznu i konzistentnu reprodukciju boja, pružajući zadivljujući vizuelni prikaz sa širokim uglovima gledanja. Sa reduktorom plavog svetla i LCD tehnologijom bez treperenja, on smanjuje naprezanje očiju, pružajući udobno iskustvo gledanja. Opremljen postoljem podesivim po visini od 150 mm koje nudi funkcije okretanja i nagibanja, omogućava lako prilagođavanje položaja ekrana prema vašim željama. Štaviše, ima ugrađenu web kameru i mikrofonom sa autofokusom od 1080p u skladu sa Windows Hello, dodajući udobnost i sigurnost vašem radnom prostoru.

### Windows Hello web kamera

Ugrađena web kamera sa mikrofonom i autofokusom garantuje besprekornu kompatibilnost sa bilo kojom platformom za video ili web konferenciju. Usklađenost sa Windows Hello omogućava korisnicima da se prijave na svoje uređaje koristeći metode biometrijske autentifikacije. Pruža zgodan i bezbedan način za pristup uređajima i aplikacijama bez potrebe za lozinkama.

### IPS Tehnologija

IPS displeji su najpoznatiji po širokim uglovima gledanja i prirodnim, izuzetno tačnim nijansama boja. Posebno su pogodni za primenu u situacijama gde je potrebno prikazati veliki broj nijansi boja.

## 01 KARAKTERISTIKE EKRANA

Dizajn	bez rama na 3 strane
Dijagonala	23.8", 60.5cm
Panel	IPS LED, mat finiš
Osnovna rezolucija	1920 x 1080 @100Hz (2.1 megapixel Full HD)
Osnovna rezolucija	100Hz
Format ekrana	16:9
Osvetljenje	250 cd/m <sup>2</sup>
Statički kontrast	1300:1
Napredni kontrast	80M:1
Vreme odziva (GTG)	4ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	16.7mln (sRGB: 99%; NTSC: 72%)
Horizontalna sinhronizacija	30 - 115KHz
Vidljiva površina Š x V	527 x 296.5mm, 20.7 x 11.7"
Razmak piksela	0.275mm
Boja	mat, crna

## 02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x1 DisplayPort x1
USB HUB	x3 (v.3.2 Gen 1 (5Gbps, DC5V, 900mA))
HDCP	da
Priključak za slušalice	da

## 03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	da
OSD jezici	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Zvučnici	2 x 2W
Pogodnost	Kensington-lock™ priprema, DDC2B, Mac OSX

## 04 MEHANIČKI

Podešavanje položaja prikaza	visina, okretanje, nagib, pivot (rotacija u obe strane)
Podešavanje visine	150mm
Rotacija (PIVOT funkcija)	90°
Okretno postolje	90°; 45° levo; 45° desno
Ugao nagiba	23° gore; 5° dole
VESA montiranje	100 x 100mm
Sistem upravljanja kablovima	da

## 05 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI
---------	-------------------------

Ostalo

kratko uputstvo, bezbednosni vodič

## 06 UPRAVLJANJE NAPAJANJEM

Napajanje

interna

Potrošnja energije

14W default , 0.5W stand by, 0.3W isključen

## 07 ODRŽIVOST

Propisi

TCO Sertifikat, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS podrška, ErP, WEEE, REACH, UKCA

Klasa energetske efikasnosti (Regulation (EU) 2017/1369)

D

REACH SVHC

iznad 0.1%: Olova

## 08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D

539.5 x 365.5 (515.5) x 209.5mm

Dimenzije kutije Š x V x D

610 x 410 x 159mm

Težina (bez kutije)

5kg

Težina (sa kutijom)

6.6kg

EAN kod

4948570123186

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IYAMA CORPORATION. ALL RIGHTS RESERVED