



## 21.5" IPS 3-side borderless monitor for multi-monitor set-ups

The stylish edge-to-edge design of the ProLite XU2293HS with IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, headphone socket, HDMI and DisplayPort connections and a blue light reducer function to reduce eye fatigue, this 21.5" ProLite display is a great choice for both multi-monitor configuration and office applications.

Available also with height adjustable stand : [ProLite XUB2293HS-B6](#)

### IPS Technology

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.

### Flicker-free + Blue light

The ultimate solution for the comfort and health of your eyes. Flicker-free monitors with the blue light reducer function substantially reduce the strain and fatigue caused by flickering and blue light emittance of regular monitors.

## 01 DISPLAY CHARACTERISTICS

|                             |   |
|-----------------------------|---|
| <b>Design</b>               | 3-side borderless   |
| <b>Diagonal</b>             | 21.5", 54.5cm   |
| <b>Panel</b>                | IPS panel technology LED, matte finish                                |
| <b>Native resolution</b>    | 1920 x 1080 @100Hz (2.1 megapixel Full HD)                            |
| <b>Aspect ratio</b>         | 16:9  |
| <b>Panel brightness</b>     | 300 cd/m <sup>2</sup>   |
| <b>Static contrast</b>      | 1000:1  |
| <b>Advanced contrast</b>    | 80M:1   |
| <b>Response time (MPRT)</b> | 1ms   |
| <b>Viewing zone</b>         | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| <b>Colour support</b>       | 16.7mIn (sRGB: 96%; NTSC: 72%)  |
| <b>Horizontal Sync</b>      | 30 - 110kHz   |
| <b>Viewable area W x H</b>  | 478.7 x 260.3mm, 18.8 x 10.3"   |
| <b>Pixel pitch</b>          | 0.249mm   |
| <b>Colour</b>               | matte, black  |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                            |   |
|----------------------------|---|
| <b>Signal input</b>        | HDMI x1 (v. 1.4)<br>DisplayPort x1 (v. 1.2) |
| <b>HDCP</b>                | yes   |
| <b>Headphone connector</b> | yes   |

## 03 FEATURES

|                              |  |
|------------------------------|--|
| <b>Blue light reducer</b>    | yes  |
| <b>Flicker free</b>          | yes  |
| <b>Adaptive Sync support</b> | yes  |
| <b>Extra</b>                 | i-style Colour   |
| <b>OSD languages</b>         | EN, DE, FR, ES, IT, PT, CN, RU, JP, CZ, NL,  |
| <b>Control buttons</b>       | Power, Menu, Up / Right / Volume, Down / Left / Eco, Signal/ Exit  |
| <b>User controls</b>         | picture adjust (brightness, contrast, i-Style colour, ACR, Eco, OD, X-Res technology), colour settings (gamma, RGB range, colour temp.), image settings (video mode adjust, blue light reducer, sharp and soft, AdaptiveSync), OSD (OSD H. position, OSD V. position, OSD time, OSD background, language, display information), extra (reset, DDC /CI, signal select, LED, opening logo) |
| <b>Speakers</b>              | 2 x 2W   |
| <b>Convenience</b>           | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX  |

## 04 MECHANICAL

|                                     |                 |
|-------------------------------------|-----------------|
| <b>Display position adjustments</b> | tilt            |
| <b>Tilt angle</b>                   | 22° up; 4° down |
| <b>VESA mounting</b>                | 100 x 100mm     |
| <b>Cable management system</b>      | yes             |

## 05 ACCESSORIES INCLUDED

|               |             |
|---------------|-------------|
| <b>Cables</b> | power, HDMI |
|---------------|-------------|

|       |                                 |
|-------|---------------------------------|
| Other | quick start guide, safety guide |
|-------|---------------------------------|

## 06 POWER MANAGEMENT

|                   |   |
|-------------------|---|
| Power supply unit | internal                                  |
| Power supply      | AC 100 - 240V, 50/60Hz                    |
| Power usage       | 17W typical, 0.5W stand by, 0.3W off mode |

## 07 SUSTAINABILITY

|   |  |
|---|--|
| Regulations   | TCO Certified, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA |
| Energy efficiency class (Regulation (EU) 2017/1369) | E  |
| REACH SVHC  | above 0.1%: Lead   |

## 08 DIMENSIONS / WEIGHT

|                              |                   |
|------------------------------|-------------------|
| Product dimensions W x H x D | 492 x 359 x 178mm |
| Box dimensions W x H x D     | 564 x 380 x 122mm |
| Weight (without box)         | 2.6kg             |
| Weight (with box)            | 3.6kg             |
| EAN code                     | 4948570124244     |