



32" IPS Panel Tehnologiji monitor sa WQHD rezolucijom

ProLite X3270QSU-B1 je ekran dijagonale 31,5" sa IPS panelom i WQHD (2560x1440) rezolucijom, koji pruža odlične performanse u boji sa širokim uglovima gledanja i primetno oštrije slike, što je idealno za rešenja za produktivnost, zahtevne kancelarijske i finansijske aplikacije. Opremljen USB čvorištem, HDMI i DisplayPort priključcima, zvučnicima, utičnicom za slušalice i funkcijom redukcije plavog svetla za smanjenje zamora očiju čine ovaj monitor od 32" odličnim izborom i za konfiguraciju sa više monitora i za kancelarijske aplikacije.

Takođe dostupan sa postoljem podesivim po visini : [ProLite XB3270QSU-B1](#)

QHD

Sa pravom QHD rezolucijom od 2560 x 1440p, Vaš monitor je spreman za prikaz slika visoke rezolucije. To znači da na Vaš ekran možete smestiti više informacija, tj. 76% više u odnosu na monitor od 1920 x 1080.

IPS Tehnologija

IPS displeji su najpoznatiji po širokim uglovima gledanja i prirodnim, izuzetno tačnim nijansama boja. Posebno su pogodni za primenu u situacijama gde je potrebno prikazati veliki broj nijansi boja.

01 KARAKTERISTIKE EKRANA

Dijagonala	31.5", 80cm
Panel	IPS Panel Technology LED, mat finiš
Osnovna rezolucija	2560 x 1440 @100Hz (3.7 megapixel WQHD)
Osnovna rezolucija	100Hz
Format ekrana	16:9
Osvetljenje	250 cd/m ²
Statički kontrast	1200:1
Napredni kontrast	80M:1
Vreme odziva (GTG)	3ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Horizontalna sinhronizacija	30 - 90KHz
Vidljiva površina Š x V	698.1 x 392.7mm, 27.5 x 15.5"
Razmak piksela	0.272mm
Boja	mat, crna

02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x1 (v.2.0) DisplayPort x1 (v.1.4)
USB HUB	x3 (v. 3.2 Gen (1, 5Gbit; 4.5W))
HDCP	da
Priključak za slušalice	da

03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	da
Dodatno	i-Style boje
OSD jezici	EN, DE, FR, IT, RU, JP, CZ, NL, PL
Kontrolni tasteri	Uključivanje, Meni/Gore/Desno/Jačina zvuka, Dole/Levo/Eko, Ulaz/Izlaz
Korisničke kontrole	podešavanje slike (osvetljenost, kontrast, i-Style boja, ACR, Eco, OD, X-Res tehnologija), podešavanja boja (gama, RGB opseg, temp. boja), podešavanja slike (podešavanje video režima, reduktor plavog svetla, oštar i meki), OSD (H. pozicija, V. pozicija, vreme, pozadina, jezik), ekstra (resetovanje, DDC / CI, LED, logo otvaranja, Adaptive Sync, informacije o ekranu), izbor ulaza (izvor), podešavanja zvuka (jačina zvuka, nemo)
Zvučnici	2 x 2W
Pogodnost	Kensington-lock™ priprema, DDC2B, Mac OSX

04 MEHANIČKI

Podešavanje položaja prikaza	nagib
Ugao nagiba	20° gore; 4° dole
VESA montiranje	100 x 100mm
Sistem upravljanja kablovima	da

05 UKLJUČENI DODACI

Kablovi

Strujni kabl, USB, HDMI

Ostalo

kratko uputstvo, bezbednosni vodič

06 UPRAVLJANJE NAPAJANJEM

Napajanje

interna

Potrošnja energije

% 1W tipično, 0.3W stand by, 0.5W isključen

07 ODRŽIVOST

Propisi

CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS podrška, ErP, WEEE, REACH, UKCA

Klasa energetske efikasnosti (Regulation (EU) 2017/1369)

E

REACH SVHC

iznad 0.1%: Olova

08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D

726 x 503.5 x 221.5mm

Dimenzije kutije Š x V x D

810 x 505 x 125mm

Težina (bez kutije)

6.9kg

Težina (sa kutijom)

8.5kg

EAN kod

4948570123643

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED