

IFP INTERACTIVE DISPLAYS**INFORMATION**

98" Google EDLA Certified IFP - Interactive display for seamless integration and collaboration in education and enterprise

The TE9813A-B1AG is a cutting-edge 4K UHD Google EDLA Certified interactive display that redefines performance and precision. Featuring a Zero Airgap LCD screen to eliminate parallax and with PureTouch-IR+ with Palm Rejection, it ensures smooth, accurate interaction.

Powered by iiWare 21E with Android 14-EDLA, WiFi-6 with Bluetooth 5.0 connectivity, and iiControl (DMS), it integrates seamlessly into your ecosystem.

Enjoy advanced wireless sharing with the intuitive iiShare app for streamlined collaboration and enjoy added features like a PIR motion sensor for energy efficiency and NFC Reader for security. Perfect for workplaces and educational spaces, it fosters collaboration, communication, and progress.

Google EDLA Certified

Google Enterprise Device License Agreement allows Google apps, accounts, files, and collaborative tools to be easily accessed directly from the Google EDLA certified iiyama displays, offering seamless integration with the Google ecosystem and the entire Microsoft 365 suite for enhanced user experience, productivity, and collaboration in all environments, especially the education and enterprise sectors alike.

iiWare 21E (Android 14 OS)

Empower your presentations with iiWare 2a1E, featuring featuring Google EDLA, iiControl (DMS), iiShare (Wireless Presentation), WhiteBoard, Cloud Drives, iiBrowser and file manager via an intuitive and user-friendly software that allows you to effortlessly manage, customize, and access various applications with ease.

Quick Radial Menu

This feature provides a quick way to operate the interactive display. Long press with five fingers to bring up the Quick Radial Menu. Users can directly select the frequently used apps in the apps menu and place them in the Quick Radial Menu.

iiControl - DMS

iiControl provides organizations with a convenient and fast unified management solution for terminal equipment, builds an efficient and real-time equipment management system, helps digitize the campus/office estate environment and makes device management ultra convenient. iiyama DMS is committed to maintaining compliance with GDPR.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	Thin bezel
Diagonal	97.5", 247.7cm
Panel	IPS
Touch Glass	Anti-Glare glass with Anti-Gloss treatment, Anti-Bacterial coating, Ultra Smooth writing, Zero Bonding
Panel	IPS
Native resolution	3840 x 2160 (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	450 cd/m ²
Light transmittance	88%
Static contrast	1200:1
Response time (GTG)	8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (NTSC 72%)
Horizontal Sync	30 - 135kHz
Viewable area W x H	2159 x 1214mm
Pixel pitch	0.562mm
Bezel colour and finish	black, matte

02 TOUCH

Touch technology	PureTouch-IR ⁺
Touch points	40, 32pt writing (HID, only with supported OS, 32pt Touch with Android)
Scan rate	200Hz
Touch accuracy	+/- 1mm
Touch method	stylus, finger, glove (Passive pen, Opaque objects)
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Palm rejection	yes

03 INTERFACES / CONNECTORS / CONTROLS

Digital signal input	HDMI x2 (2.0, max. 3840x2160 @60Hz, YUV444, ARC on HDMI #1) DisplayPort x1 (1.2, max. 3840x2160 @60Hz) USB-C x2 (3.2 (Gen 1, 5Gbit), 3840x2160 @60Hz (RGB444), DP 1.2 Alt mode, 100W PD (1x front (network sharing 100M, 1x side), Data, Touch)
Audio input	Mini jack x1 (Microphone)
Monitor control input	RS-232c x1 (DSUB 9pin)

Digital signal output	HDMI x1 (2.0, max. 3840x2160 @60Hz, YUV444 / RGB444, MSD (Multi-Screen Display))
Audio output	S/PDIF (Optical) x1 Mini jack x1 (Headphone) Speakers 2 x 20W (Front facing + 20W Subwoofer)
Monitor control output	OPS Slot x1 (Intel OPS 80pin)
HDCP	2.3
USB ports	x5 (media playback / peripherals / storage – front side: 2x 3.2 (Gen 1, 5Gbit.), 1x USB-C 3.2 (Gen 1, 5Gbit, 100W PD), side: 1x 3.2 (Gen 1, 5Gbit, 1x USB-C v.3.2 (Gen 1, 5Gbit, 100W PD))
RJ45 (LAN)	x2 (IN / OUT, Auto switch for PC & Android, 1000MB)

04 FEATURES

Integrated software	iiWare 21E (Android 14 OS) featuring Google EDLA, iiControl (DMS), WhiteBoard, web browser, file manager, cloud drives and iiShare for wireless connection with Windows/iOS/Android devices
WiFi	yes (WiFi-6, Bluetooth 5.0)
Hardware	CPU: Quad-core A73*4 (1.4GHz), GPU: G52 MC1, RAM: 8GB, ROM: 128GB
Extra	Ambiant light Sensor, NFC Reader, PIR Motion Sensor, Slot for optional OPS PC, 4x Touch pen (anti-bacterial coating)
Kiosk mode	yes
Max. non-stop operating time	18/7
Media playback	yes
Glass thickness	4mm
Glass hardness	7H
Housing (bezel)	metal
OSD key lock	yes

05 GENERAL

OSD languages	EN, DE, FR, ES, IT, RU, CZ, NL, PL, SV, FI, DA, NB
Control buttons	Power, Home, Touch-freeze, Volume, Input (source)
User controls	general settings (input, volume, backlight), audio (volume, bass, treble, balance, sound mode, mute), screen settings (aspect ratio, pixel shift), display settings (brightness, contrast, hue, sharpness, display mode colour temp), settings (wireless & networks, share, device, personal, system)
Blue light reducer	yes
Flicker free	yes
Plug&Play	DDC2B
Warranty	5 years (for details and eligible countries please check the Warranty section of our website)

06 MECHANICAL

Orientation	landscape
Fanless design	yes

VESA mounting	800 x 600mm
Operation temperature range	0°C - 40°C
Storage temperature range	- 20°C - 60°C
MTBF	50.000 hours (excluding backlight)

07 ACCESSORIES INCLUDED

Cables	power (EU 3m, UK 3m), USB (3m), HDMI (3m)
Touch pen	x4 (Dual function tips, anti-bacterial coating)
Guides	quick start guide, safety guide
Other	Wall Mounting Bracket (VESA 800x600), Webcam Mounting Bracket
Remote control	yes (batteries included)

08 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	303W typical, 0.5W stand by, 0.3W off mode

09 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, EPEAT, REACH (RoHS)
REACH SVHC	above 0.1%: Lead

10 DIMENSIONS / WEIGHT

Product dimensions W x H x D	2235.4 x 1326 x 103mm
Box dimensions W x H x D	2360 x 1445 x 280mm
Weight (without box)	109.6kg
Weight (with box)	132.2kg
EAN code	4948570124831

11 COMPATIBLE ACCESSORIES

Other OPS Slot PC, MD-CAR2031-B1, MD-WLIFT2031-W1, UC-CAM10PRO-1, UC-SPK01L

GALLERY

TE9813A-B1AG(20).jpg

TE9813A-B1AG(10).jpg

TE9813A-B1AG(21).jpg

TE9813A-B1AG(30).jpg



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED