

65" 4K UHD professional digital signage display with advanced control and connectivity options

Elevate your visual communication with the LH6564UHS-B1AG and unlock the new possibilities for your business. This 500cd/m² high brightness display is a powerful business tool that takes your marketing and communication efforts to the next level. With its Android 14 OS, [iiSignage²](#) (CMS), [iiControl](#) (DMS), [iiShare](#) (Wireless Presentation) and Signal FailOver features, this display offers a straightforward user experience, making content creation, management, and sharing a breeze. WiFi enabled, the display is ready for remote content delivery using your network or you can choose to utilise LAN control.

Its versatile orientation, sleek design including wall mounting bracket, and 24/7 reliability ensure it seamlessly integrates into any business environment. Whether it's used in retail, corporate, hospitality, or restaurant settings, the LH64 SERIES will undoubtedly captivate your audience and leave a lasting impression.

Android OS

Thanks to Android OS, you can easily customize the display to your needs by installing applications directly to it.

iiSignage²

iiSignage² is our digital signage content management platform to easily show and control your content and to manage your displays in a secure way. The Content Management System (CMS) gives you total control of your messaging and advertising remotely and safely.

Signal FailOver

FailOver is a feature which automatically detects input sources. When there is no signal on the default input it will automatically switch to the next available input. FailOver allows customers to prioritize a number of inputs (incl. Browser, Media Player and Custom) and ensures your content is always actively displayed, assuring active content at all times.

Flexible Orientation

With the option to switch between landscape and portrait mode, these displays let you get creative with any space. Whether it's messaging, ads, videos, or safety info, you can tailor your content to grab attention exactly how you want.

SPECIFIKÁCIÓ

01 KIJELZŐ JELLEMZŐI

Dizájn	Vékony káva
Átló	65", 164cm
Panel	VA, Anti-Glare coated glass, matte finish, haze 25%
Natív felbontás	3840 x 2160 @60Hz (8.3 MegaPixels 4K UHD)
Képarány	16:9
Fényerő	500 cd/m ²
Statikus kontraszt	5000:1
Válaszidő (GTG)	6.5ms
Látótér	horizontális/vertikális: 178°/178°, jobb/bal: 89°/89°, fel/le: 89°/89°
Szín támogatás	1.07G (8 Bits+FRC)
Horizontális szinkronizálás	57 - 62kHz
Látható terület Sz x M	1428.5 x 803.5mm, 56.2 x 31.6"
Káva szélessége (oldal, felső, alsó)	14mm, 14mm, 14mm
Pixel magasság	0.372mm
Káva színe és felülete	fekete, matt

02 INTERFÉSZEK / CSATLAKOZÓK / VEZÉRLŐK

Digitális jelmemenet	HDMI x2 (v.2.0, max. 3840x2160 @60Hz) USB-C x1 (DP Alt, 15W PD)
Monitor vezérlő bemenet	RS-232c x1 (2.5mm sub-mini jack) RJ45 (LAN) x1 IR x1 (3.5mm stereo mini)
Audio kimenet	Mini jack x1 (3.5mm) Hangszórók 2 x 10W
Monitor vezérlő kimenet	RS-232c x1 (2.5mm) IR loop through csatlakozó x1 (3.5mm)
HDCP	v.1.4 & 2.0
USB portok	x2 (v.2.0)

03 JELLEMZŐK

Beépített szoftver	Android 14 OS, iiSignage ² , iiControl, iiShare, FailOver, TeamViewer, PDF & Media Player, iiBrowser, File manager
WiFi	igen (Built-in, 2.4G/ 5G)
Hardver	CPU: A73*4, GPU: G52 MC1, RAM: 4GB, ROM: 32GB
Extra	Wall mounting kit included (VESA 500x500mm)
Max. non-stop üzemidő	24/7
Anti képmegőrzés	igen
Média lejátszás	igen

Ház (káva)	fém
------------	-----

04 ÁLTALÁNOS

Képernyőn megjelenő nyelvek EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL, SV, FI, DA, NB

Vezérlógombok	Power Indicator, Power button, Remote Sensor
----------------------	--

Felhasználói vezérlők network (status, Wifi, ethernet, hotspot), picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temp., colour control, picture reset), audio (balance, treble, bass, volume, audio out, max. volume, min. volume, mute, audio out sync, speaker setting, audio reset), OSD setting (OSD timeout, OSD H-Position, OSD V-position, OSD transparency, information OSD), general (logo and animation, wallpaper, no signal image, schedule, off timer), screen (zoom mode, custom zoom, system rotation, screen reset), device (power on status, RS232 routing, IR control, power saving, panel saving, monitor info, other), channel (boot on source, rename input channel, auto source switching, signal lost detection, HDMI version), system (language, system update, setting reset, factory reset, Android setting), admin (menu lock, meeting room, HDMI CEC, screen share, Miracast standby, log export)

Plug&Play	DDC2B
----------------------	-------

05 MECHANIKUS

Tájolás tájkép, portré

Ventilátor nélküli kialakítás	igen
--------------------------------------	------

VESA állvány 500 x 500mm

Működési hőmérséklet tartomány	0°C - 40°C
---------------------------------------	------------

Tárolási hőmérséklet tartomány - 20°C - 60°C

MTBF	50.000 óra (kivéve háttérvilágítás)
-------------	-------------------------------------

06 TARTOZÉKOKAT TARTALMAZZA

Kábelek áramellátás, HDMI, RS-232c

Útmutatók gyors üzembe helyezési útmutató, biztonsági útmutató

Egyéb Wall mount bracket, Wall mount guide, Screws, Screw anchors, Stickers for screw holes

Távírányító igen (elemeket tartalmazza)

07 ENERGIAGAZDÁLKODÁS

Tápegység belső

Áramellátás AC 100 - 240V, 50/60Hz

Energiafogyasztás 184W jellemző, 0.5W készenlét, 0.3W kikapcsolva

Áramfogyasztás 0.5W készenlét

08 FENNTARTHATÓSÁG

Előírások CE, TÜV-Bauart, EAC, RoHS támogatás, ErP, WEEE, HATÓTÁVOLSÁG (UKCA, RoHS2.0, PFOS)

Energiatahatékonyági
osztály ((EU)
2017/1369 rendelet)

G

09 MÉRTEK / SÚLY

Termék méretei Sz x H x M 1457.7 x 832.4 x 68.8mm

Doboz méretei Sz x H x M 1640 x 990 x 164mm

Súly (doboz nélkül) 17.7kg

Súly (dobozsal) 27.5kg

EAN kód 4948570125326

LH6564UHS-B1AG(20).jpg LH6564UHS-B1AG(10).jpg

LH6564UHS-B1AG(11).jpg LH6564UHS-B1AG(12).jpg

LH6564UHS-B1AG(12)1.jpg LH6564UHS-B1AG(30).jpg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED