



Get ahead with the curved GCB3484WQSU-B1 Red Eagle featuring 180Hz refresh rate and 0.4ms response time

Immerse yourself in the ultimate gaming experience with the 34" GCB3484WQSU-B1 curved gaming monitor. Designed with a 1500R curvature, it wraps around your field of view for a more engaging and comfortable experience. The VA panel with an ultra-wide 3440x1440 resolution delivers deep contrasts and vibrant colors, making every detail stand out.

With an impressive 180Hz refresh rate, motion is smooth and fluid, providing top-tier performance. The fast 0.4ms response time (MPRT) minimises motion blur, ensuring crisp and precise gameplay. HDR400 enhances brightness and contrast for more lifelike visuals, while FreeSync Premium reduces screen tearing and stuttering for a seamless experience.

Additionally, the monitor features both Picture-in-Picture (PiP) and Picture-by-Picture (PbP) functions, allowing you to multitask efficiently and enhance your workflow. Whether you're gaming, streaming, or working, the monitor adapts to your needs.

CURVED DESIGN 1500R

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.

180Hz & 0.4ms MPRT

With 180Hz refresh rate and 0.4ms MPRT response time the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.

01 DISPLAY CHARACTERISTICS

Design	curved
Diagonal	34", 86.4cm
Panel	VA
Curved	1500R
Native resolution	3440 x 1440 @180Hz (4.9 megapixel UWQHD, DisplayPort)
Aspect ratio	21:9
Panel brightness	500 cd/m ²
Static contrast	4000:1
Advanced contrast	80M:1
Response time (MPRT)	0.4ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mln 8bit (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 285kHz
Viewable area W x H	797.22 x 333.72mm, 31.4 x 13.1"
Pixel pitch	0.232mm
Colour	black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0b, 3440x1440 @100Hz) DisplayPort x1 (v.1.4, 3440 x 1440@ 180Hz)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium - HDMI: 2560 x 1440 @48-120Hz, DP: 3440 x 1440 @48-180Hz, VRR / ALLM
HDR	HDR400
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power Indicator, Joystick: Power / Menu (Center), Up / Signal Select, Down, Left / i-Style Colour / Night Mode / Blue Light Reducer, Right / Volume
User controls	picture adjust (contrast, brightness, OD, HDR, FreeSync Premium, ACR, Night Mode, Blue Light Reducer, Motion Blur Reduction, Gamma), input select, audio settings (volume, mute), store user settings (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style Colour, x-res technology, sharpness, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED, DDC/CI control, USB charge, PIP/PBP), display information, reset
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	150mm

Tilt angle 23° up; 5° down

VESA mounting 100 x 100mm

Cable management system yes

05 ACCESSORIES INCLUDED

Cables power (1.85m), USB (1.5m), HDMI (1.85m), DP (1.85m)

Other quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit internal

Power supply AC 100 - 240V, 50/60Hz

Power usage 60W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369) F

REACH SVHC above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D 808 x 433 (578) x 290mm

Box dimensions W x H x D 982 x 490 x 190mm

Weight (without box) 8.5kg

Weight (with box) 13kg

EAN code 4948570125166

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IYAMA CORPORATION. ALL RIGHTS RESERVED