



Black Hawk - get in the game

Capable of displaying Full HD images at 75Hz, the 27" Black Hawk G-MASTER GB2730HSU is the perfect companion in your gaming adventures. Armed with Black Tuner function and FreeSync Technology with a stunning 1 ms response time, the Black Hawk guarantees you will see every tiny detail even in the shadowed screen areas and will be able to respond to the changing situation in an instant. The height adjustable stand with pivot, swivel and tilt functions allows you to perfectly adjust the position of the screen to your preferences. So get comfortable and get in the game! If 27" is too big for you, check out the 24.5" Black Hawk GB2530HSU-B1.

FreeSync™ Technology

1ms

Fast response time is key to ultra-smooth gaming. It reduces ghosting and blurring providing the user with an improved graphic performance.



Diagonal	27", 68.6cm
Panel	TN LED, matte finish
Native resolution	1920 x 1080 @75Hz (2.1 megapixel Full HD, HDMI&DisplayPort)
Aspect ratio	16:9
Panel brightness	300 cd/m ²
Static contrast	1000:1
Advanced contrast	80M:1
Response time (GTG)	1ms
Viewing zone	horizontal/vertical: 170°/160°, right/left: 85°/85°, up/down: 80°/80°
Colour support	16.7mln (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 84kHz
Viewable area W x H	597.6 x 336.15mm, 23.5 x 13.2"
Pixel pitch	0.311mm
Colour	matte



02 INTERFACES / CONNECTORS / CONTROLS

Signal input	VGA x1 (max. 1920 x 1080 @60Hz) HDMI x1 (v.1.4, max. 1920 x 1080 @75Hz) DisplayPort x1 (v.1.2, max. 1920 x 1080 @75Hz)
USB HUB	x2 (v.2.0)
HDCP	yes
Headphone connector	yes



Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	HDMI & DP: 1920 x 1080 @40-75Hz
OSD languages	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL
Control buttons	Power, Input/ Select, Scroll up/ Audio Adjust, Scroll down/ i-Style Mode, Menu
User controls	picture adjust (contrast, brightness, OverDrive, ACR, ECO), input select, audio adjust (volume, mute, HDMI audio input), store user setting, colour adjust, manual image adjust (i-style mode, H.V. position, clock, phase, sharpness, black tuner, HDMI RGB range, video mode adjust, blue light reducer), setup menu (language select, FreeSync, OSD position, OSD time out, OSD background, LED, opening logo, auto image adjust), information, memory recall
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX



04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	130mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right
Tilt angle	22° up; 5° down
VESA mounting	100 x 100mm



Cables	power, USB, HDMI
Other	quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	19.7W typical, 0.3W stand by, 0.27W off mode

07 SUSTAINABILITY

REACH SVHC

Regulations	CE, TÜV-GS, RoHS support, ErP, ENERGY STAR®, WEEE, CU, REACH
Energy efficiency class (Regulation (EU) 2017/1369)	E

above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	613.5 x 412 (542) x 230mm
Weight (without box)	7.3kg
EAN code	4948570116515

© IIYAMA CORPORATION. ALL RIGHTS RESERVED