

Wireless presentation HDMI dongle KIT

The wireless presentation dongle allows to share content (e.g. videos, applications) from your computer to an iiyama 42-series LFD with the EShare app pre-installed. It is compatible with computers equipped with HDMI (version 1.4) and USB outputs and supports smooth video streaming up to 1080p.

The kit contains also the [EW-7811UTC](#) wireless dual-band mini USB adapter which you need to connect to the LFD to use the dongle.

01 DEVICE

Supported platforms	Windows, MAC, Chrome, any OS supporting HDMI standard 1.4
HDMI Out	x1
Audio	stereo, radio quality 16bits 48kHz
Frame rate	up to 60 fps depending on environment (FHD)
Output resolution	720x480, 720x576, 1280x720, 1920x1080
Input resolution	Video: 480p, 576p, 720p, 1080p PC timing: 640x480, 800x600, 1024x768, 1280x720, 1920x1080
Wireless	IEEE 802.11ac, 5GHz, IEEE 802.11n, 2.4GHz
Data rate wireless	up to 867Mbps
Authentication protocol	WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise)
Security (encryption)	WPA2
Reach	15 m max.

02 POWER MANAGEMENT

Power usage	2.5W typical
--------------------	--------------

03 SUSTAINABILITY

Regulations	CE, RoHS support
--------------------	------------------

04 DIMENSIONS / WEIGHT

EAN code	4948570032549
-----------------	---------------

05 ENVIRONMENTAL CONDITIONS

Operation temperature range	0°C - 40°C
Operation humidity	10% - 80%
Storage temperature range	- 10°C - 60°C
Storage humidity	5% - 90%

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED