

## Wireless presentation HDMI dongle KIT

The wireless presentation dongle allows to share content (e.g. videos, applications) from your computer to an iiyama 42-series LFD with the EShare app pre-installed. It is compatible with computers equipped with HDMI (version 1.4) and USB outputs and supports smooth video streaming up to 1080p.

The kit contains also the [EW-7811UTC](#) wireless dual-band mini USB adapter which you need to connect to the LFD to use the dongle.

### 01 DEVICE

<b>Supported platforms</b>	Windows, MAC, Chrome, any OS supporting HDMI standard 1.4
<b>HDMI Out</b>	x1
<b>Audio</b>	stereo, radio quality 16bits 48kHz
<b>Frame rate</b>	up to 60 fps depending on environment (FHD)
<b>Output resolution</b>	720x480, 720x576, 1280x720, 1920x1080
<b>Input resolution</b>	Video: 480p, 576p, 720p, 1080p PC timing: 640x480, 800x600, 1024x768, 1280x720, 1920x1080
<b>Wireless</b>	IEEE 802.11ac, 5GHz, IEEE 802.11n, 2.4GHz
<b>Data rate wireless</b>	up to 867Mbps
<b>Authentication protocol</b>	WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise)
<b>Security (encryption)</b>	WPA2
<b>Reach</b>	15 m max.

### 02 POWER MANAGEMENT

<b>Power usage</b>	2.5W typical
--------------------	--------------

### 03 SUSTAINABILITY

<b>Regulations</b>	CE, RoHS support
--------------------	------------------

### 04 DIMENSIONS / WEIGHT

<b>EAN code</b>	4948570032549
-----------------	---------------

## 05 ENVIRONMENTAL CONDITIONS

<b>Operation temperature range</b>	0°C - 40°C
<b>Operation humidity</b>	10% - 80%
<b>Storage temperature range</b>	- 10°C - 60°C
<b>Storage humidity</b>	5% - 90%

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED