

## An Intel® i5 slot PC with Windows® 10 IoT Enterprise

This mini PC with Intel® Core™ i5 inside turns your iiyama interactive large format display into a stand-alone solution. It comes equipped with a powerful Intel® processor with integrated Ultra HD graphics and a fast SSD drive. No hassle with cables and having to mount a PC at the back of the monitor or on a floor lift. Simply slide in the iiyama slot PC and get started right away.

The module is only compatible with the iiyama TExx03MIS and TExx04MIS\* Series; 55": [TE5503MIS-B1AG](#) / [TE5503MIS-B2AG](#), 65": [TE6503MIS-B1AG](#) / [TE6504MIS-B1AG](#) / [TE6504MIS-B2AG](#), 75": [TE7503MIS-B1AG](#) / [TE7504MIS-B1AG](#) / [TE7504MIS-B2AG](#), 86": [TE8603MIS-B1AG](#) / [TE8604MIS-B1AG](#) / [TE8604MIS-B2AG](#), 98": [TE9803MIS-B1AG](#)

\*Excluding the 98" [ProLite TE9804MIS-B1AG](#)

### 01 DEVICE

|                  |   |
|------------------|---|
| Type             | slot PC                                 |
| CPU              | Intel® Core™ i5-8400                    |
| RAM              | 8GB DDR4                                |
| SSD              | 256GB M.2                               |
| Graphics         | Intel® HD Graphics 630                  |
| Chipset          | Intel® H310                             |
| Sound card       | Integrated High Definition Audio Stereo |
| Networking       | 10/100/1000M Adapter                    |
| WiFi             | 802.11ac (2.4GHz/5GHz)                  |
| Bluetooth        | 4.2                                     |
| Operating system | Win 10 IoT Enterprise 64-bit            |
| LAN (RJ45)       | x1                                      |
| USB              | 3.0 x4, 2.0 x2, 3.1 Type C x1           |
| VGA Out          | x1                                      |
| DisplayPort Out  | x1                                      |
| HDMI Out         | x1                                      |
| Microphone In    | x1                                      |

### 02 POWER-MANAGEMENT

|                        |                              |
|------------------------|------------------------------|
| <b>Napájecí zdroj:</b> | interní                      |
| <b>Napájení</b>        | AC 100 - 240V, 50/60Hz       |
| <b>Odběr energie:</b>  | 95W typisch, 1.35W odpočinek |

### 03 ROZMĚRY / HMOTNOST

|                                  |                        |
|----------------------------------|------------------------|
| <b>Rozměry výrobku Š x V x D</b> | 263.4 x 32.2 x 246.1mm |
| <b>Rozměry balení Š x V x D</b>  | 312 x 91 x 353mm       |
| <b>Váha (bez balení)</b>         | 1.9kg                  |
| <b>EAN code</b>                  | 4948570032723          |

### 04 ENVIRONMENTAL CONDITIONS

|                                |               |
|--------------------------------|---------------|
| <b>Rozsah provozní teploty</b> | 0°C - 45°C    |
| <b>Operation humidity</b>      | 10% - 90%     |
| <b>Rozsah teploty v klidu</b>  | - 20°C - 60°C |
| <b>Storage humidity</b>        | 10% - 90%     |

*Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED