

UNIFIED COMMUNICATIONS**All-in-one conference bar**

Simplify your meetings via one collaboration solution, equipped with 12MP camera, 6 array microphone and 8W speakerphone. Intelligent face detection, auto tracking and voice localization provide seamless meeting experiences whilst zoom in/out and up to 3 camera position presets are all controlled using the remote control.

120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.

Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.

Camera position presets

Three predefined camera presets combined with 5x digital zoom allow for instant meeting start up. Just point the camera to your preferred focal point, save it and select between the saved options with one button when needed.

Studio-quality sound

6-element Microphone & 8W Speakerphone featuring Adaptive echo canceller, Automatic tracking, Noise reduction, Automatic gain control & Dereverberation deliver crisp, high quality sound free from any background noise or distortion.

SPECIFICATION

01 CAMERA

Pixels	12M
Nativní rozlišení	4K UHD
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Diagonal field of view (dFoV)	120°
Focus mode	fixed
Focus distance	2m
Zoom	5x digital zoom
AutoFraming	ano
Number of camera position presets	3

02 DŹWIĘK

Number of microphone arrays	6
Voice pickup distance	8m
Adaptive echo canceller	ano
Automatic tracking	ano
Noise reduction	ano
Automatic gain control	ano
Dereverberation	ano
Reproduktory	1 x 8W

03 CONNECTIVITY

Camera	USB Type-C
Audio In/Out	x1

04 ZAHRNUTÉ PŘÍSLUŠENSTVÍ

Wall mount	ano
Anti peeping cover	ano
Dálkové ovládání	ano (včetně baterie)
Power adapter	ano

05 UDRŽITELNOST

Předpisy CE, RoHS support, ErP, WEEE, REACH

06 ROZMĚRY / HMOTNOST

Rozměry výrobku Š x V x D 462 x 76 x 93mm

Rozměry balení Š x V x D 538 x 160 x 169mm

Váha (bez balení) 1kg

Váha (s balením) 2.3kg

EAN code 4948570032983

07 SOUVÍSEJÍCÍ INFORMACE

Související produkty [UC CAM120UL-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC CAM75FS-1](#), [UC SPK01M](#), [UC SPK01L](#)

GALERIE

UC CAM120ULB(20).jpg

UC CAM120ULB(10).jpg

UC CAM120ULB(30).jpg

UC CAM120ULB(11).jpg



Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů. © IYAMA CORPORATION. ALL RIGHTS RESERVED