

UNIFIED COMMUNICATIONS

- INFORMATION

All-in-one conference bar

Simplify your meetings via one collaboration solution, equipped with 12MP camera, 6 array microphone and 8W speakerphone. Intelligent face detection, auto tracking and voice localization provide seamless meeting experiences whilst zoom in/out and up to 3 camera position presets are all controlled using the remote control.

120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.

Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.

Camera position presets

Three predefined camera presets combined with 5x digital zoom allow for instant meeting start up. Just point the camera to your preferred focal point, save it and select between the saved options with one button when needed.

Studio-quality sound

6-element Microphone & 8W Speakerphone featuring Adaptive echo canceller, Automatic tracking, Noise reduction, Automatic gain control & Dereverberation deliver crisp, high quality sound free from any background noise or distortion. SPECIFICATION

01 CAMERA

| Pixels | 12M |
|-----------------------------------|---------------------------------------|
| Native resolution | 4K UHD |
| Supported resolutions | 2160p/30fps, 1440p/30fps, 1080p/30fps |
| Diagonal field of view (dFoV) | 120° |
| Focus mode | fixed |
| Focus distance | 2m |
| Zoom | 5x digital zoom |
| AutoFraming | yes |
| Number of camera position presets | 3 |



| Number of microphone arrays | 6 |
|--------------------------------|--------|
| Voice pickup distance | 8m |
| Adaptive echo canceller | yes |
| Automatic tracking | yes |
| Noise reduction | yes |
| Automatic gain control | yes |
| Dereverberation | yes |
| Speakers | 1 x 8W |



CONNECTIVITY

Audio In/Out x1

04 ACCESSORIES INCLUDED

Wall mount yes

| Anti peeping cover | yes | |
|--------------------|--------------------------|--|
| Remote control | yes (batteries included) | |
| Power adapter | yes | |
| | | |

SUSTAINABILITY

Regulations CE, RoHS support, ErP, WEEE, REACH



DIMENSIONS / WEIGHT

| Product dimensions W x H x D | 462 x 76 x 93mm |
|---------------------------------|-------------------|
| Box dimensions W x H x D | 538 x 160 x 169mm |
| Weight (without box) | 1kg |
| Weight (with box) | 2.3kg |
| EAN code | 4948570032983 |

| GA | EC | v | |
|----|--------|-----|--|
| GP | .сг | 1 I | |

| UC CAM120ULB(20).jpg | UC CAM120ULB(10).jpg |
|----------------------|----------------------|
| UC CAM120ULB(30).jpg | UC CAM120ULB(11).jpg |
| | |
| | |

© IIYAMA CORPORATION. ALL RIGHTS RESERVED