

UNIFIED COMMUNICATIONS

— INFORMATION

4K panoramic camera with auto tracking technology

With 180° field of view, the 13 mega pixel UC CAM180UM makes sure everything important stays on camera. Six predefined video layouts are easily accessible at your fingertip with one button, and an integrated 2 microphone array detects audio from up to 4 metres away.

The auto tracking technology not only recognizes and zooms in on meeting participants, but it also follows the speakers as they move about the room. Compatible with all the leading conferencing software like Zoom, Skype, Microsoft Teams and others.

180° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 180-degree FoV makes everybody at the table clearly visible, even those close to the camera or seated at the edges of the room.

Six predefined video layouts

Simply tap the top of the camera to switch between the different layout options. From one-way lecturing to multi-party brainstorming, this camera can cover it all.

Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.

Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

01 CAMERA

| | |
|-------------------------------|---------------------------------------|
| PanoCam Studio Software | да |
| Pixels | 12M |
| Разрешение | 4K UHD |
| Supported resolutions | 2160p/24fps, 1440p/30fps, 1080p/30fps |
| Diagonal field of view (dFoV) | 180° |
| Focus mode | fixed |
| Focus distance | 1.5m |
| Aperture | 2.2 |
| AutoFraming | да |

02 AUDIO

| | |
|-----------------------------|------|
| Number of microphone arrays | 2 |
| Voice pickup distance | 4m |
| Voice pickup angle | 180° |

03 CONNECTIVITY

| | |
|---------|------------|
| Camera | USB Type-C |
| USB out | да |

04 6. АКСЕССУАРЫ

Wall mount да

05 СТАНДАРТЫ

Сертификаты CE, RoHS support, ErP, WEEE, REACH

06 РАЗМЕР / ВЕС

| | |
|---------------------------|------------------|
| Размер продукта Ш x В x Г | 144 x 73 x 26мм |
| Размер коробки Ш x В x Г | 175 x 175 x 44мм |
| Вес (без упаковки) | 0.2кг |
| Вес (с упаковкой) | 0.5кг |
| EAN код | 4948570033027 |

Сопутствующие UC CAM120ULB-1, UC CAM120UL-1, UC CAM80UM-1, UC CAM75FS-1, UC SPK01M,
товары UC SPK01L

ГАЛЕРЕЯ

UC-CAM180UM(20).jpg

UC-CAM180UM(10).jpg

UC-CAM180UM(11).jpg

UC-CAM180UM(30).jpg

Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей. © IIYAMA CORPORATION. ALL RIGHTS RESERVED