

UNIFIED COMMUNICATIONS**INFORMATION****Bluetooth Speakerphone for meeting rooms**

The omnidirectional audio pickup from up to 3 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01M the perfect choice for medium meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this elegant speaker can be paired with up to 3 devices at the same.

Omnidirectional

The UC SPK01M supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.

High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.

Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.

Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

SPECIFICATION

01 SPEAKER

Maximum sound pressure level	85dB
Distortion	≤1%
Signal to noise ratio	75dB
Frequency range	150Hz ~ 16kHz

02 MICROPHONE

Number of microphone arrays	x3
Voice pickup range	3m (radius)
Frequency range	150Hz ~ 7.5kHz

03 CONNECTIVITY & BUTTON OPERATIONS

USB Type C	x1 (Audio In/Out, Charge 5V/2A)
AUX	x1 (In/Out, 3.5mm)
Bluetooth	4.2+EDR
Buttons	Power, Volume, Bluetooth, Mute, Answer/Hang up

04 ACCESSORIES & BATTERY

Bluetooth receiver	yes
USB (type A to C) cable	yes
Audio cable	yes
Battery capacity	7.4V/2200mAh
Charging	wired 5V/2A
Battery life on a single charge	8 hours

05 SUSTAINABILITY

Regulations CE, RoHS support, ErP, WEEE, REACH

06 DIMENSIONS / WEIGHT

Weight (without box)	0.39kg
EAN code	4948570033034

GALLERY

UC-SPK01M (20).jpg

UC-SPK01M (10).jpg

UC-SPK01M (30).jpg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © **IYAMA CORPORATION. ALL RIGHTS RESERVED**