

UNIFIED COMMUNICATIONS**INFORMATION****Bluetooth Speakerphone for
large meeting rooms**

The omnidirectional audio pickup from up to 5 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01L the perfect choice for large meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this sleek looking speaker can be paired with up to 3 devices at the same.

Omnidirectional

The UC SPK01L supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.

High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.

Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.

Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

ХАРАКТЕРИСТИКИ

01 SPEAKER

| | |
|------------------------------|---------------|
| Maximum sound pressure level | 85dB |
| Distortion | ≤4% |
| Signal to noise ratio | 80dB |
| Frequency range | 150Hz ~ 16kHz |

02 МИКРОФОН

| | |
|-----------------------------|--------------|
| Number of microphone arrays | x6 |
| Voice pickup range | 5m (radius) |
| Frequency range | 150Hz ~ 8kHz |

03 CONNECTIVITY & BUTTON OPERATIONS

| | |
|------------|--|
| USB Type C | x1 (Audio In/Out, Charge 5V/2A) |
| AUX | x1 (In/Out, 3.5mm, DaisyChain) |
| Bluetooth | 4.2+EDR |
| Buttons | Power, Volume, Bluetooth, Mute, Answer/Hang up |

04 ACCESSORIES & BATTERY

| | |
|---------------------------------|--------------------------|
| Bluetooth receiver | да |
| USB (type A to C) cable | да |
| Audio cable | yes |
| Battery capacity | 7.4V/2200mAh |
| Charging | wired 5V/2A, wireless 5W |
| Battery life on a single charge | 8 hours |

05 СТАНДАРТЫ

Сертификаты CE, RoHS support, ErP, WEEE, REACH

06 РАЗМЕР / ВЕС

| | |
|--------------------|---------------|
| Вес (без упаковки) | 0.4кг |
| EAN код | 4948570033041 |

07 СОПУТСТВУЮЩАЯ ИНФОРМАЦИЯ

Сопутствующие UC CAM120ULB-1, UC CAM120UL-1, UC CAM180UM-1, UC CAM80UM-1, UC
товары CAM75FS-1, UC SPK01M

UC SPK01L (30).jpg

UC SPK01L (10).jpg

UC SPK01L (20).jpg

UC SPK01L (50).jpg

UC SPK01L (40).jpg

Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей. © IIYAMA CORPORATION. ALL RIGHTS RESERVED