



Oslobodite svoj puni gejmerski potencijal uz pomoć brzog IPS G2770QSU Red Eagle-a

Dobijte konkurentsku prednost koja vam je potrebna da oslobodite svoj puni potencijal za igranje sa 27-inčnim G2770QSU koji nudi MPRT od 0,5 ms i brzinu osvežavanja od 165 Hz. Naoružani FreeSync Premium Pro možete da donosite odluke u deliću sekunde i zaboravite na gosting efekte ili probleme sa zamagljivanjem slike. Mogućnost podešavanja osvetljenosti i tamnih nijansi sa black tuner-om, pruža bolje performanse gledanja u zasenčenim područjima, a IPS tehnologija panela garantuje vrhunski kvalitet slike.

Brzi IPS

Tehnologija Fast IPS panela garantuje ne samo visoke vernosti prikaza, živopisne scene bojnog polja koje se prikazuju sa izvanrednom preciznošću boja, već takođe pruža izvanredno vreme odziva na pokretnu sliku (MPRT) od 0,5 ms.

Freesync™ Premium Pro Tehnologija

Ovaj monitor podržava reprodukciju HDR sadržaja sa pažljivim odnosom boje i osvetljenja. Niska latencija ulaza i kompenzacija brzine kadra zaustavljaju sve probleme sa kidanjem slike ili kasnjenjem na gotovo bilo kojoj frekvenciji.

01 KARAKTERISTIKE EKRANA

Dijagonala	27", 68.5cm
Panel	Brzi IPS, mat završna obrada
Osnovna rezolucija	2560 x 1440 @165Hz (3.7 megapixel WQHD, DisplayPort)
Osnovna rezolucija	165Hz
Format ekrana	16:9
Osvetljenje	400 cd/m ²
Statički kontrast	1000:1
Napredni kontrast	80M:1
Vreme odziva (MPRT)	0.5ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	16.7miliona 8bit
Horizontalna sinhronizacija	30 - 242KHz
Vidljiva površina Š x V	596.7 x 335.6mm, 23.5 x 13.2"
Razmak piksela	0.233mm
Boja	mat, crna

02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x1 (v.2.0, max. 2560 x 1440 @144Hz) DisplayPort x1 (v.1.4, max. 2560 x 1440 @165Hz)
USB HUB	x2 (v.3.2 (Gen 1, 5Gbit; DC5V, 900mA))
HDCP	da
Priključak za slušalice	da

03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	FreeSync Premium Pro - HDMI: 2560 x 1440 @40-144Hz, DP: 2560 x 1440 @40-165Hz
HDR	400
OSD jezici	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Korisničke kontrole	podešavanje slike (kontrast, osvetljenje, overdrive, ACR, ECO, reduktor plave svetlosti, black tuner, zasićenost boja, MBR, gama), izbor ulaza, podešavanje zvuka (jačina zvuka, isključivanje zvuka), čuvanje korisničkih podešavanja, podešavanja boje (temperatura boje, 6 - Osa, korisnička podešavanja), podešavanje slike (i-Style boja, X-Res tehnologija, oštro i meko, RGB opseg, podešavanje video režima), jezik, meni za podešavanje (OSD H. pozicija, OSD V. pozicija, rotacija OSD-a, OSD vremensko ograničenje, logo otvaranja, AMD FreeSync Premium Pro, LED), prikaz informacija, resetovanje
Zvučnici	2 x 2W
Pogodnost	Kensington-lock™ priprema, DDC2B, Mac OSX

04 MEHANIČKI

Podešavanje položaja prikaza	nagib
Ugao nagiba	21.5° gore; 3.5° dole
VESA montiranje	100 x 100mm
Sistem upravljanja kablovima	da

05 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI, DP
Ostalo	kratko uputstvo, bezbednosni vodič

06 UPRAVLJANJE NAPAJANJEM

Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W isključen

07 ODRŽIVOST

Propisi	CE, TÜV-Bauart, EAC, PSE, RoHS podrška, ErP, WEEE, VCCI, REACH, UKCA
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	E
REACH SVHC	iznad 0.1%: Olova

08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	614 x 442 x 239mm
Težina (bez kutije)	4.4kg
EAN kod	4948570121069

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED