



HDMI adapter za wireless prezentaciju

Adapter za bežičnu prezentaciju omogućava deljenje sadržaja (npr. Video zapisa, aplikacija) sa vašeg računara na iiyama LFD računare 42 serije sa unapred instaliranom aplikacijom EShare. Kompatibilan je sa računarima opremljenim HDMI (verzija 1.4) i USB izlazima i podržava neometano strimovanje videa do 1080p. Da biste koristili adapter, potreban vam je i bežični dvopojasni mini USB adapter EV-7811UTC spojen na LFD. Možete ga kupiti odvojeno ili odabrati KIT verziju koja sadrži oba proizvoda.

01 UREDJAJ

Podržane platforme	Windows, MAC, Chrome, bilo koji OS koji podržava HDMI standard 1.4
HDMI izlaz	x1
Audio	stereo, radio kvalitet 16bits 48kHz
Broj slika	do 60 fps u zavisnosti od okruženja (FHD)
Izlazna rezolucija	720x480, 720x576, 1280x720, 1920x1080
Ulazna rezolucija	Video: 480p, 576p, 720p, 1080p PC timing: 640x480, 800x600, 1024x768, 1280x720, 1920x1080
Bežični	IEEE 802.11ac, 5GHz, IEEE 802.11n, 2.4GHz
Brzina bežičnog prenosa podataka	do 867Mbps
Protokol provere autentičnosti	WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise)
Bezbednost (enkripcija)	WPA2
Domašaj	15 m max.

02 UPRAVLJANJE NAPAJANJEM

Potrošnja energije	% 1W tipično
--------------------	--------------

03 ODRŽIVOST

Propisi	CE, RoHS podrška
---------	------------------

04 DIMENZIJE / TEŽINA

EAN kod	4948570032501
---------	---------------

05 USLOVI ŽIVOTNE SREDINE

Opseg radne temperature	0°C - 40°C
Vlažnost vazduha (u radu)	10% - 80%
Raspon temperature skladištenja	- 10°C - 60°C
Vlažnost vazduha (skladištenje)	5% - 90%

06 POVEZANE INFORMACIJE

Srodni proizvodi [EW-7811UTC](#), [WP D001HU KIT](#)

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED