



43" large format desktop monitor with 4K resolution, offering you the power of four displays packed into one

The ProLite X4373UHSU-B1 is a 43" Ultra HD 4K monitor with PbP (picture-by-picture) function allowing for simultaneous display of content from up to four different signal inputs. Divided into four, the screen offers users a dashboard equal to four Full HD displays and no bezel interrupting your view, whilst saving hassle with multiple cables. The VA panel technology guarantees an impressive view, consistent colour reproduction, superb clarity and wide 178° viewing angles. Flicker free technology and the Blue light reducer functions help to reduce eye fatigue and ensure user comfort even on long days. The HDMI, DisplayPort, USB hub and a headphone connector ensure compatibility across various devices and media platforms. Whether you work with pro editing tools, need a huge canvas for graphs and figures or are in a controlled retail environment, increase your productivity with a single iiyama X4373UHSU.



PbP (picture-by-picture)

The PbP (picture-by-picture) function allows for simultaneous display of content from up to four different signal inputs. Divided into four, the screen offers users a workplace equal to four Full HD displays put together without the bezel getting in your view and saving you the hassle with extra cables. It's perfect for a huge range of applications like stock market data, medical desktop publishing, CAD/CAM drawings, graphic and web design.



4K

UHD resolution (3840x2160), better known as 4K, offers a gigantic viewable area with 4 times more information and work space than a Full HD screen. Due to the high DPI (dots per inch), it displays an incredibly sharp and crisp image.

01 DISPLAY CHARACTERISTICS

| | |
|---------------------|---|
| Diagonal | 42.5", 108cm |
| Panel | VA matrix, matte finish |
| Native resolution | 3840 x 2160 @60Hz |
| Aspect ratio | 16:9 |
| Panel brightness | 400 cd/m ² |
| Static contrast | 4000:1 |
| Advanced contrast | 80M:1 |
| Response time (GTG) | 3ms |
| Viewing zone | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support | 1.07B 10bit (8bit + Hi-FRC) (NTSC: 85%) |
| Horizontal Sync | 30 - 135kHz |
| Viewable area W x H | 941.18 x 529.42mm, 37.1 x 20.8" |
| Pixel pitch | 0.245mm |
| Colour | matte, black |

02 INTERFACES / CONNECTORS / CONTROLS

| | |
|---------------------|--|
| Signal input | HDMI x2 DisplayPort x1 mDP x1 |
| Signal output | DisplayPort x1 (daisy chain) |
| USB HUB | x4 (v.3.2 (Gen 1, 5Gbit) x2, v.2.0 x2) |
| HDCP | yes |
| Headphone connector | yes |

03 FEATURES

| | |
|--------------------|---|
| Blue light reducer | yes |
| Flicker free | yes |
| Extra | headphone hook |
| HDR | yes |
| OSD languages | EN, DE, FR, ES, IT, PT, RU, JP, NL, PL |
| Control buttons | Input Select, Up, Down, Menu, Power |
| User controls | picture adjust (brightness, contrast, ECO, blue light reducer, advanced contrast, overdrive, black tuner), image settings (video mode adjust, sharp and soft, X-Res technology), colour settings (gamma, 6-axis, colour temperature, i-Style colour), PiP/PbP (PiP/PbP mode, sub win 1/2/3/4 input, PiP size, PiP position, swap), signal select, audio settings (volume, mute, audio input), OSD settings (OSD H. position, OSD V. position, OSD time, language), extra (reset, HDR, HDMI range, DDC/CI, opening logo, LED, DP daisy chain, information) |
| Speakers | 2 x 7W |
| Convenience | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX |

04 MECHANICAL

| | |
|------------------------------|-----------------|
| Display position adjustments | tilt |
| Tilt angle | 10° up; 2° down |
| VESA mounting | 200 x 100mm |

05 ACCESSORIES INCLUDED

| | |
|----------------|---------------------------------|
| Cables | power, USB, HDMI, DP |
| Other | quick start guide, safety guide |
| Remote control | yes (batteries included) |

06 POWER MANAGEMENT

| | |
|-------------------|---|
| Power supply unit | internal |
| Power supply | AC 100 - 240V, 50/60Hz |
| Power usage | 92W typical, 0.5W stand by, 0.5W off mode |

07 SUSTAINABILITY

| | |
|---|--|
| Regulations | CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA |
| Energy efficiency class (Regulation (EU) 2017/1369) | G |
| REACH SVHC | above 0.1%: Lead |

08 DIMENSIONS / WEIGHT

| | |
|------------------------------|-----------------------|
| Product dimensions W x H x D | 977.5 x 621.5 x 251mm |
| Box dimensions W x H x D | 1071 x 760 x 240mm |
| Weight (without box) | 14.5kg |
| Weight (without stand) | 12.7kg |
| Weight (with box) | 19kg |
| EAN code | 4948570118519 |



