



## Immerse yourself in the game with the curved GC2480HSU Red Eagle with 180Hz refresh rate

The 1500R curved VA panel with 180Hz refresh rate and 0.5ms MPRT gives you an immersive viewing experience and guarantees superb image quality. Enhanced by the Black Tuner function, it provides detailed visibility in dark scenes, allowing you to spot every detail, even in low-light settings.



### CURVED DESIGN 1500R

The 1500R curvature of the screen guarantees a realistic and comfortable viewing experience allowing you to really immerse yourself in the game.



### 180Hz & 0.5ms MPRT

With 180Hz refresh rate and 0.5ms MPRT response time the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.

## 01 DISPLAY CHARACTERISTICS

Diagonal	23.6", 59.8cm
Panel	VA
Curved	1500R
Native resolution	1920 x 1080 @180Hz (2.1 megapixel)
Aspect ratio	16:9
Panel brightness	300 cd/m <sup>2</sup>
Static contrast	3000:1
Advanced contrast	80M:1
Response time (MPRT)	0.5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn (sRGB: 96%, NTSC: 72%)
Horizontal Sync	30 - 200kHz
Viewable area W x H	521.4 x 293.3mm, 20.5 x 11.5"
Pixel pitch	0.271mm
Colour	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v. 2.0) DisplayPort x1 (v. 1.4)
USB HUB	x2 (v.2.0 (DC5V, 500mA))
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
HDR	yes
OSD languages	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Control buttons	Power, Menu (Up / Submenu, Down / Input Select, Left / ECO, Right / Volume)
User controls	picture adjust (contrast, brightness, OD, ACR, ECO, black tuner, colour saturation, motion blur red., AMD FreeSync), input source, audio settings (volume, mute audio), store user settings (user modes), colour settings (6-Axis, gamma, blue light reducer, colour temperature, user preset), image adjust (i-Style Colour, x-res technology, sharpness, RGB range, video mode adjust), language, setup menu (OSD horizontal position, OSD vertical position, OSD time, opening logo, power LED), information, recall
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

## 04 MECHANICAL

Display position adjustments	tilt
Tilt angle	22° up; 4° down
VESA mounting	100 x 100mm
Cable management system	yes

## 05 ACCESSORIES INCLUDED

Cables	power (1.5m), USB (1.5m), HDMI (1.5m)
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	21W typical, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	E
REACH SVHC	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	535.5 x 394.5 x 202mm
Box dimensions W x H x D	622 x 408 x 171mm
Weight (without box)	3.8kg
Weight (with box)	6kg
EAN code	4948570124503