



Android OS

Zahvaljujući Android operativnom sistemu, ekran možete lako prilagoditi svojim potrebama instaliranjem aplikacija direktno na njega.



Daisy Chain podrška

Daisy Chain je šema povezivanja u kojoj je nekoliko uređaja spojeno u nizu ili u prstenu. Omogućuje povezivanje niza uređaja koristeći jednu vezu između dva uređaja putem kabla. Izlaz signala povezan je sa ulazom signala sledećeg uređaja. Povezivanje samo jednim kablom između dva uređaja osigurava jednostavnu i urednu instalaciju.

01 KARAKTERISTIKE EKRANA

Dizajn	Tanki okvir
Panel	IPS LED, antiglare surface treatment, haze 1%
Vreme odziva (GTG)	12ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Horizontalna sinhronizacija	30 - 83KHz
Boja okvra	crna, mat

02 KONEKTORI / KONTROLE

Ulaz digitalnog signala	DVI x1 HDMI x2 DisplayPort x1
-------------------------	-------------------------------------

03 KARAKTERISTIKE

Integrirani softver	Android OS
Dodatno	micro USB slot, micro SD slot, USB charger (5V/2A)
Maksimalno neprekidno radno vreme	24/7
Video zid / daisy chain	yes

04 OPŠTE

Kontrolni tasteri	Power, Mute, Input, +, -, Up, Down, Menu
Korisničke kontrole	picture (brightness, contrast, sharpness, black level, tint, colour, noise reduction, gamma selection, colour temp., colour control, picture mode, overscan, reset), screen (H. position, V. position, clock, phase, zoom mode, custom zoom, auto adjust, screen reset), audio (balance, treble, bass, volume, audio out, max. volume, min. volume, mute, audio source, sync. volume, reset), PIP (sub mode, PIP size, PIP position, PIP change, PIP source, PIP audio, PIP reset), configuration1 (switch on state, panel saving, RS232 routing, boot on source, WOL, LED, reset, factory reset), configuration2 (OSD turn off, OSD H. position, OSD V. position, OSD transparency, information OSD, logo, monitor ID, heat status, monitor information, DP version, window selection, rotation, language, reset), advanced option (input resolution, IR control, keyboard control, tiling, off timer, date and time, schedule, HDMI with one wire, auto signal detection, power save, scalar FW update, USB cloning, reset), settings (ethernet, signage display, system tools, storage, apps, date and time, about)

05 ODRŽIVOST

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED