

38 SERIES

BUILD BETTER INTERACTIVE EXPERIENCES



The 38-series (TFxx38MCS/UHSC-B1AG/B2AG) is designed for seamless integration and maximum flexibility with the Open Frame side mounting holes, landscape, portrait and face-up orientation and 24/7 operating time.

Engineered to last with the ball-drop proof, scratch resistant, edge-to-edge glass and PCAP touch technology; allowing you to build the best kiosk and interactive experiences. Available in sizes from 32 to 65 inch.

KIOSK-READY / SEAMLESS INTEGRATION

Build the interactive kiosk of your dreams with the Open Frame mounting holes, curved edges and the edge-to-edge glass; ensuring a seamless integration and perfect fit without any gaps.

READY TO PERFORM

Whether you install them in landscape, portrait or face-up; with their 24/7 operating time, scratch-resistant 7H hardened and ball drop proof glass, the 38-series displays can handle even the toughest, most-demanding environments.

SHOW PERFECT IMAGES

The 38 series displays come with IPS panels, FULL HD and 4K UHD resolutions and anti-glare coating to ensure it is the content on the display that gets seen.

ENJOY LONG-LASTING ACCURACY

The durable multi-touch Projective Capacitive (PCAP) touch technology guarantees an accurate and flawless touch experience for years to come.



38 SERIES



	TF3238MSC-B2AG/W2AG	TF4338MSC-B2AG	TF4938UHSC-B2AG	TF5538UHSC-B2AG/W2AG	TF6538UHSC-B2AG
Diagonal	31.5" (80 cm)	43" (108 cm)	48.5" (123.2 cm)	55" (139 cm)	65" (165 cm)
Panel type	AMVA3			IPS	
Panel coating	glossy; anti-glare coating				
Resolution	1920 x 1080 (Full HD)		3840 x 2160 (4K UHD)		
Brightness typical (cd/m ²)	420	380	420		
Orientation	landscape / portrait / face-up				
Operation time	24/7				
Glass thickness / hardness	3mm / 7H		4mm / 7H		5mm / 7H

Touch technology	Projective Capacitive (PCAP)				
Touch points / Palm rejection	12 / yes		15 / yes		50 / yes

Video IN	VGA, DVI, 2 x HDMI, DisplayPort				
Video OUT	-				
Audio IN	MiniJack				
Audio OUT	MiniJack, speakers 2 x 8W				
Controls	RS232C (IN/OUT), RJ45 (LAN CONTROL), USB Touch, IR (IN/OUT)				
Dimensions (w x h x d) / Weight	748.5 x 450 x 68 mm / 14.5 kg	987.5 x 587.7 x 68 mm / 21.5 kg	1154.1 x 684.3 x 73.4 mm / 30 kg	1294.5 x 765.5 x 67.5 mm / 41 kg	1530.5 x 905.5 x 67.5 mm / 59.8 kg
Bezel width (mm)	27.3 / 23.8 / 23.8	28 / 22 / 22	38.8 / 39 / 38	41.3 / 41.3 / 41.3	49.8 / 49.8 / 49.8

Extra features	Open Frame, RS232c (Get/Set), metal bezel, 60950-1 ball drop test proof, IP54				
Available colours	black/white	black		black / white	black
Energy efficiency class	B	A	C	B	B