



Wireless AC1200 Dual-Band MU-MIMO mini USB 3.0 Adapter

Upgrade your wireless device to dual-band 802.11ac with the fastest possible USB 3.0 connectivity for blistering WiFi speeds on the interference free 5Ghz frequency band. The Edimax EW-7822UTC is the next generation of WiFi adapter, compatible with the draft 802.11ac standard and delivering speeds of up to 867Mbps at 5GHz - almost three times as fast as 802.11n.

Upgrade the professional large format displays of the TF39AS SERIES to super high speed 802.11ac WiFi and enjoy streaming video and data.

Supporting MU-MIMO, the EW-7822UTC allows greater WiFi efficiency and has a one-click WiFi Protected Setup (WPS) button to help you set up and activate a secure wireless network in a snap.

For more details, please click [HERE](#)

01 DEVICE

WiFi	AC1200 WiFi 5, Max. data transfer rates up to 867Mbps (5GHz) and 300Mbps (2.4GHz)
Operating system	Windows 7/8/8.1/10, Mac OS 10.9 - 10.15 and Linux Kernel: 2.6.24 ~ 4.15

02 TECHNICAL SPECIFICATION

WiFi standard	2.4GHz: IEEE 802.11b/g/n, 5GHz: IEEE 802.11ac/a/n
---------------	---

03 ПАМЯТЬ / БЕС

Размер продукта	8 x 16 x 34мм
Вес (без упаковки)	0.04кг
EAN код	4717964701619

04 ENVIRONMENTAL CONDITIONS

Диапазон рабочих температур	0°C - 40°C
Operation humidity	0% - 90%
Диапазон температур хранения	- 20°C - 60°C
Storage humidity	0% - 95%

Сопутствующие товары

[ProLite TF3239MSC-B1AG](#), [ProLite TF4339MSC-B1AG](#), [ProLite TF6539AS-B1AG](#), [ProLite TF5039AS-B1AG](#), [ProLite TF5539AS-B1AG](#)

Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED