



### 34" curved ultra-wide screen with 15cm height adjustable stand

The ProLite XCB3493WQSU is a 34-inch curved monitor with a VA panel, delivering high contrast, deep blacks, and wide viewing angles for consistent image quality from any perspective. UWQHD (Ultra-Wide QHD) resolution provides an ultra-wide (21:9) viewable area. The large amount of screen space and good pixel density make it very suitable for those who want to use side-by-side applications, watch widescreen content or enhance their gaming experience.

For added comfort and flexibility, the 15cm height-adjustable stand allows you to adjust the screen position to your preference. Additionally, flicker-free technology and a blue light reducer function reduces eye fatigue.



#### VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



#### **CURVED DESIGN 1500R**

The 1500R curvature of the screen reduces the strain on your eyes while providing a realistic viewing experience. It allows a comprehensive and more natural viewing angle than you'll have with flat monitors lined up side by side. The result is a more immersive experience which boosts productivity and focus whether it be for work, gaming, entertainment, editing or more.

# 01 DISPLAY CHARACTERISTICS

Diagonal   34", 86.7cm     Panel   VA panel, matte finish     Curved   1500R     Native resolution   3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort)     Aspect ratio   21:9     Panel brightness   350 cd/m²     Static contrast   3000:1     Advanced contrast   80M:1     Response time (MPRT)   0.4ms     Viewing zone   horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°     Colour support   16.7mln (sRGB: 99%; NTSC: 93%)     Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"     Pixel pitch   0.232mm	Design	curved
Curved   1500R     Native resolution   3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort)     Aspect ratio   21:9     Panel brightness   350 cd/m²     Static contrast   3000:1     Advanced contrast   80M:1     Response time (MPRT)   0.4ms     Viewing zone   horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°     Colour support   16.7mln (sRGB: 99%; NTSC: 93%)     Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"	Diagonal	34", 86.7cm
Native resolution3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort)Aspect ratio21:9Panel brightness350 cd/m²Static contrast3000:1Advanced contrast80M:1Response time (MPRT)0.4msViewing zonehorizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°Colour support16.7mln (sRGB: 99%; NTSC: 93%)Horizontal Sync30 - 180kHzViewable area W x H797.2 x 333.7mm, 31.3 x 13.1"	Panel	VA panel, matte finish
Aspect ratio 21:9   Panel brightness 350 cd/m²   Static contrast 3000:1   Advanced contrast 80M:1   Response time (MPRT) 0.4ms   Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°   Colour support 16.7mln (sRGB: 99%; NTSC: 93%)   Horizontal Sync 30 - 180kHz   Viewable area W x H 797.2 x 333.7mm, 31.3 x 13.1"	Curved	1500R
Panel brightness350 cd/m²Static contrast3000:1Advanced contrast80M:1Response time (MPRT)0.4msViewing zonehorizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°Colour support16.7mln (sRGB: 99%; NTSC: 93%)Horizontal Sync30 - 180kHzViewable area W x H797.2 x 333.7mm, 31.3 x 13.1"	Native resolution	3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort)
Static contrast   3000:1     Advanced contrast   80M:1     Response time (MPRT)   0.4ms     Viewing zone   horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°     Colour support   16.7mln (sRGB: 99%; NTSC: 93%)     Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"	Aspect ratio	21:9
Advanced contrast 80M:1   Response time (MPRT) 0.4ms   Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°   Colour support 16.7mln (sRGB: 99%; NTSC: 93%)   Horizontal Sync 30 - 180kHz   Viewable area W x H 797.2 x 333.7mm, 31.3 x 13.1"	Panel brightness	350 cd/m²
Response time (MPRT)   0.4ms     Viewing zone   horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°     Colour support   16.7mln (sRGB: 99%; NTSC: 93%)     Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"	Static contrast	3000:1
Viewing zone   horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°     Colour support   16.7mln (sRGB: 99%; NTSC: 93%)     Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"	Advanced contrast	80M:1
Colour support   16.7mln (sRGB: 99%; NTSC: 93%)     Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"	Response time (MPRT)	0.4ms
Horizontal Sync   30 - 180kHz     Viewable area W x H   797.2 x 333.7mm, 31.3 x 13.1"	Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Viewable area W x H 797.2 x 333.7mm, 31.3 x 13.1"	Colour support	16.7mln (sRGB: 99%; NTSC: 93%)
·	Horizontal Sync	30 - 180kHz
Pixel pitch 0.232mm	Viewable area W x H	797.2 x 333.7mm, 31.3 x 13.1"
·	Pixel pitch	0.232mm
Colour matte, black	Colour	matte, black

## 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (1x v.2.0 and 1x v. 1.4, 3440x1440 @100Hz, 2560x1440 @120Hz) DisplayPort x1 (v.1.4, 3440 x $$ 1440 @120Hz)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
HDCP	yes
Headphone connector	yes

## 03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium - HDMI: 2560 x 1440 @48-120Hz, DP: 3440 x 1440 @48-120Hz
Extra	i-Style Colour
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Joystick: Power/ Menu (Centre), Forward/ Signal Select, Backward, Left/ i-Style colour/ ECO/ Blue Light Reducer, Right/ Volume
User controls	picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync, motion blur reduction, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.,), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, USB C speed), input select, audio settings (volume, mute audio), recall
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC2B

# 04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	150mm
Swivel stand	90°; 45° left; 45° right

Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes



### **ACCESSORIES INCLUDED**

Cables	power, USB, HDMI, DP
Other	quick start guide, safety guide



### POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	55W typical, 0.5W stand by, 0.3W off mode



### SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	above 0.1%: Lead



### **DIMENSIONS / WEIGHT**

Product dimensions W x H x D	807 x 426 (576) x 245.5mm
Box dimensions W x H x D	940 x 500 x 198mm
Weight (without box)	9.7kg
Weight (with box)	13.8kg
EAN code	4948570125135

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED