



Budite ispred svih uz GB2745QSU sa IPS Panel tehnologijom i 1ms MPRT

Preпустите се изузетној изврѕnosti video igrica sa 27" GB2745QSU monitorom. Ovaj ekran se moųe pohvaliti najsavremenijom IPS tehnologijom panela, WQHD rezolucijom (2560x1440), brzinom osveųavanja od 100 Hz i ultra-brzim MPRT vremenom odziva od 1 ms. Podignite svoju avanturu igranja na sledeći nivo, zahvaljujući funkciju Black Tuner, koja obezbeđuje kristalno јasnu vidljivost čak i u najmраčnijim scenama. Pored toga, opremljen je visokim podesivim postolјem (15 cm).

Takođe dostupan sa fiksnim postolјem : [G-Master G2745HSU-B2 \(1920x1080\)](#) i [G-Master G2745QSU-B2 \(2560x1440\)](#)



1ms

Brzo vreme odziva ključno je za glatko igranje. Ono smanjuje ghosting i razmazivanje slike, a korisniku pruųa bogato iskustvo uz pobolјšane performanse.



100Hz

Brzina osvežavanja od 100 Hz se pretvara u povećanu glatkoću slike. To znači da je treperenje smanjeno, a samim tim i zamor očiju manje primetan. Povećana frekvencija takođe znači glatkije prelaze između kontrastnih boja, ugađeniije scene pokreta u filmovima i igrama, pa čak i smanjeno treperenje kursora miša.

01 KARAKTERISTIKE EKRANA

Dijagonala	27", 68.5cm
Panel	IPS, mat završna obrada
Osnovna rezolucija	2560 x 1440 @100Hz (2.1 megapixel)
Osnovna rezolucija	100Hz
Format ekrana	16:9
Osvetljenje	300 cd/m ²
Statički kontrast	1300:1
Napredni kontrast	80M:1
Vreme odziva (MPRT)	1ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	16.7miliona 8bit
Horizontalna sinhronizacija	30 - 151KHz
Vidljiva površina Š x V	596.7. x 335.7mm, 23.5 x 13.2"
Razmak piksela	0.233mm
Boja	mat, crna

02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x1 (v.2.0) DisplayPort x1 (v.1.2)
USB HUB	x2 (v.3.2 DC5V, 900mA)
HDCP	da
Priključak za slušalice	da

03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	Adaptive Sync - 2560 x 1440 @48-100Hz
Dodatno	i-Style Boja
OSD jezici	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Kontrolni tasteri	Uključivanje, meni, jačina zvuka, crni tjuner / MBR / adaptivna sinhronizacija / noćni režim, izbor ulaza / izlaz
Korisničke kontrole	podešavanje slike (kontrast, osvetljenost, OD, AC, Eco, Black Tuner, zasićenost boja, MBR, adaptivna sinhronizacija), izvor ulaza, audio podešavanja (jačina zvuka, isključivanje zvuka), korisnički režimi, podešavanja boja (6-osovina, gama, plava reduktor svetlosti, temperatura boje, korisnička podešavanja), podešavanje slike (i-Style Colour, oštra i meka, RGB opseg, podešavanje video režima), jezik, meni za podešavanje (OSD h. pozicija, OSD v. pozicija, OSD rotacija, OSD vreme, logo otvaranja, LED), informacije o prikazu, opoziv
Zvučnici	2 x 2W
Pogodnost	Kensington-lock™ priprema, DDC2B, Mac OSX

04 MEHANIČKI

Podešavanje položaja prikaza	okretanje, nagib, pivot (rotacija u obe strane)
Podešavanje visine	150mm
Rotacija (PIVOT funkcija)	90°
Okretno postolje	45°; 45° levo; 45° desno

Ugao nagiba	23° gore; 5° dole
VESA montiranje	100 x 100mm
Sistem upravljanja kablovima	da

05 UKLJUČENI DODACI

Kablovi	Strujni kabl (1.5m), USB (1.5m), HDMI (1.5m), DP (1.8m)
Ostalo	kratko uputstvo, bezbednosni vodič

06 UPRAVLJANJE NAPAJANJEM

Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W isključen

07 ODRŽIVOST

Propisi	CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS podrška, ErP, WEEE, REACH, UKCA
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	E
REACH SVHC	iznad 0.1%: Olova

08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	611.5 x 555.5 x 214mm
Dimenzije kutije Š x V x D	691 x 142 x 447mm
Težina (bez kutije)	5.5kg
Težina (sa kutijom)	7.2kg
EAN kod	4948570124756

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED