# iiyama



#### An Intel® i5 slot PC with Windows® 10 IoT Enterprise

This mini PC with Intel® Core™ i5 inside turns your iiyama interactive large format display into a stand-alone solution. It comes equipped with a powerful Intel® processor with integrated Ultra HD graphics and a fast SSD drive. No hassle with cables and having to mount a PC at the back of the monitor or on a floor lift. Simply slide in the iiyama slot PC and get started right away.

The module is only compatible with the iiyama TExx03MIS and TExx04MIS\* Series; 55": <u>TE5503MIS-B1AG</u> / <u>TE5503MIS-B1AG</u> / <u>TE5503MIS-B1AG</u> / <u>TE5504MIS-B2AG</u> , 75": <u>TE7503MIS-B1AG</u> / <u>TE7504MIS-B1AG</u> /

\*Excluding the 98" ProLite TE9804MIS-B1AG

## 01 DEVICE

| Туре             | slot PC                                 |
|------------------|-----------------------------------------|
| CPU              | Intel® Core™ i5-8400                    |
| RAM              | 8GB DDR4                                |
| SSD              | 256GB M.2                               |
| Graphics         | Intel® HD Graphics 630                  |
| Chipset          | Intel® H310                             |
| Sound card       | Integrated High Definition Audio Stereo |
| Network          | 10/100/1000M Adapter                    |
| WiFi             | 802.11ac (2.4GHz/5GHz)                  |
| Bluetooth        | 4.2                                     |
| Operating system | Win 10 IoT Enterprise 64-bit            |
| LAN (RJ45)       | x1                                      |
| USB              | 3.0 x4, 2.0 x2, 3.1 Type C x1           |
| VGA Out          | x1                                      |
| DisplayPort Out  | x1                                      |
| HDMI Out         | x1                                      |
| Microphone In    | x1                                      |

| Power supply unit | internal                    |
|-------------------|-----------------------------|
| Power supply      | AC 100 - 240V, 50/60Hz      |
| Power usage       | 95W typical, 1.35W stand by |

#### 03 DIMENSIONS / WEIGHT

| Product dimensions W x H x D | 263.4 x 32.2 x 246.1mm |
|------------------------------|------------------------|
| Box dimensions W x H x D     | 312 x 91 x 353mm       |
| Weight (without box)         | 1.9kg                  |
| EAN code                     | 4948570032495          |

### 04 ENVIRONMENTAL CONDITIONS

| Operation temperature range | 0°C - 45°C    |
|-----------------------------|---------------|
| Operation humidity          | 10% - 90%     |
| Storage temperature range   | - 20°C - 60°C |
| Storage humidity            | 10% - 90%     |

#### 05 RELATED INFORMATION

**Related products** 

SPC5801BB, SPC5802BB

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED