



## 98" Interactive 4K UHD LCD Touchscreen with integrated annotation software

Share Your Vision with the ProLite TE9803MIS-B1AG; a perfect solution for educational and corporate use. The 98" infrared 20-point touchscreen with iiWare 8.0 (Android OS) featuring Note, web browser, file manager, cloud drives, WPS office and ScreenSharePro. It comes with dual touch pens, allowing users to annotate easily in 4K on files and on-screen content, which can be saved directly on a USB device, 16gig internal memory or on a connected cloud drive. The display supports playback of presentations, high-resolution video and almost any other type of content.

The high-quality commercial IPS LCD screen with 4K UHD resolution (3840x2160 - 8.3 megapixel), 350cd/m<sup>2</sup> and a contrast ratio of 1200:1 provides vibrant, detailed and high-quality images from anywhere in the class- or meeting room. The anti-glare coating drastically reduces ambient reflection in high-brightness environments without compromising the sharpness and clarity of the image. The screen is equipped with an all-metal bezel and 4mm thick hardened glass to ensure long durability in high-use environments, such as classrooms or meeting rooms.

Share, stream and edit content from any device directly on screen and transform your team meetings or lessons into an easy, fast and seamless interactive session with the included WiFi module ([OWM001](#)) and the ScreenSharePro app.



### iiWare 8.0 (Android OS)

iiWare 8.0 features 6 different applications for collaboration and content sharing, plus it contains Note, a web browser, file manager, cloud drive manager, WPS Office and ScreenSharePro. Note is the digital whiteboard app for 4K annotations on screen as well as in content and with ScreensharePro users can share, stream and capture content from any device directly on screen and transform team meetings or lessons into easy, fast and seamless interactive sessions. iiWare supports presentation playback, high-resolution video and almost any other type of content from a USB drive, online or internal memory.



### Slot PC

Transform your display into a stand-alone solution with the optional slot PC\*.

No more hassle with cables and having to mount a NUC or PC at the back of the monitor or on the floor lift. Simply slide in an iiyama slot PC (sold separately) and get started right away.

*\*Not suited for OPS Slot PC's.*

## 01 DISPLAY CHARACTERISTICS

Design	Thin bezel
Diagonal	98", 247.7cm
Panel	IPS Direct LED, AG coated glass
Native resolution	3840 x 2160 (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	350 cd/m <sup>2</sup>
Light transmittance	88%
Static contrast	1200:1
Dynamic contrast	4000:1
Response time (GTG)	8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit
Horizontal Sync	30 - 80kHz
Viewable area W x H	2158.9 x 1214.4mm, 85 x 47.8"
Pixel pitch	0.562mm
Bezel colour and finish	black, matte

## 02 TOUCH

Touch technology	infrared
Touch points	20 (HID, only with supported OS)
Touch accuracy	+/- 2mm
Touch method	stylus, finger, glove
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.

## 03 INTERFACES / CONNECTORS / CONTROLS

Analog signal input	VGA x1 (max. 1920x1080 @60Hz)
Digital signal input	HDMI x3 (v.2.0, max. 3840x2160 @60Hz (YUV420))
Audio input	Mini jack x1
Monitor control input	RS-232c x1 RJ45 (LAN) x1 (Internet for Android only)
Digital signal output	HDMI x1 (2.0, 3840x2160 @60Hz)
Audio output	S/PDIF (Optical) x1 Mini jack x1 Speakers 2 x 12W
HDCP	v.2.2
USB ports	x6 (media playback / peripherals / storage - front: 2x v.2.0, bottom: 1x v.2.0, right side: 3x v.3.0)

## 04 FEATURES

Integrated software	iiWare 8.0 (Android OS) featuring Note, web browser, file manager, cloud drives, WPS office and ScreenSharePro for wireless connection with Windows/iOS/Android devices
WiFi	yes (WiFi Module OWM001 - Dual WiFi Bandwidth: 2.4GHz/5GHz, WiFi Standard: 11AC 802.11 a/b/g/n/ac)

<b>Hardware</b>	Dual core A73+A53 CPU, Quad core Mali G51 GPU, 3GB RAM, 16GB internal memory
<b>Extra</b>	WiFi Module (OWM001), slot for optional slot PC, four touch pens
<b>Kiosk mode</b>	yes
<b>Max. non-stop operating time</b>	18/7
<b>Media playback</b>	yes
<b>Glass thickness</b>	4mm
<b>Glass hardness</b>	7H
<b>Housing (bezel)</b>	metal
<b>OSD key lock</b>	yes

## 05 GENERAL

<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, CZ, NL, PL
<b>User controls</b>	general settings (input, volume, backlight), audio setting (volume, bass, treble, balance, sound mode, mute), screen setting (aspect ratio, pixel shift), display setting (brightness, contrast, hue, sharpness, display mode, colour temp), adjust setting (H-position, V-position, clock, phase, auto), settings (wireless & networks, share, device, personal, system)
<b>Plug&amp;Play</b>	DDC2B
<b>Warranty</b>	5 years (for details and eligible countries please check the Warranty section of our website)

## 06 MECHANICAL

<b>Orientation</b>	landscape
<b>Fanless design</b>	yes
<b>VESA mounting</b>	800 x 600mm
<b>Operation temperature range</b>	0°C - 40°C
<b>Storage temperature range</b>	- 20°C - 60°C
<b>MTBF</b>	50.000 hours (excluding backlight)

## 07 ACCESSORIES INCLUDED

<b>Cables</b>	power, USB, HDMI
<b>Touch pen</b>	x4 (ø3 x2 & ø7 x2)
<b>Guides</b>	quick start guide, safety guide
<b>Remote control</b>	yes (batteries included)

## 08 POWER MANAGEMENT


<b>Power supply unit</b>	internal
<b>Power supply</b>	AC 100 - 240V, 50/60Hz
<b>Power usage</b>	196W typical, 0.5W stand by, 0.5W off mode

## 09 SUSTAINABILITY

<b>Regulations</b>	CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH
<b>REACH SVHC</b>	above 0.1%: Lead

## 10 DIMENSIONS / WEIGHT

Product dimensions W x H x D	2244.7 x 1323 x 90.5mm
Box dimensions W x H x D	2483 x 1493 x 376mm
Weight (without box)	101.5kg
Weight (with box)	138.75kg
EAN code	4948570117772



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED