

UNIFIED COMMUNICATIONS**INFORMATION****4K Conference webcam for 120-degree FOV and autoframing**

With 120° field of view, the 8 mega pixel UC CAM120UL featuring 2D and 3D denoising technologies delivers sensational smoothness and detail, even in low light conditions and makes sure everything important stays on camera. An integrated 2 microphone array detects audio from up to 4 meters away.

Easy to set-up and supporting 360-degree horizontal rotation with 10 degree angle adjustment, this lightweight camera works in any and every environment large or small whilst supporting all leading conferencing software like Zoom, Skype, Microsoft Teams and more.



120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.



2D & 3D Digital Noise Reduction with HDR

Delivering high image quality, these two image denoising technologies combined ensure crisp and clear visuals for video and photos, even in low light conditions. And to make sure everyone from your team is always clearly visible, regardless of the ambient lighting conditions, the high dynamic range (HDR) technology automatically adjusts brightness level to keep you in the spotlight.



Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.



Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.

01 CAMERA

Pixels	8M
Разрешение	4K UHD
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Diagonal field of view (dFoV)	120°
Focus mode	fixed
Focus distance	1.5m
Aperture	1.8
AutoFraming	да

02 AUDIO

Number of microphone arrays	2
Voice pickup distance	4m
Voice pickup angle	180°

03 CONNECTIVITY

Camera	USB Type-C
Host	USB v.2.0

04 МЕХАНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Угол наклона экрана	≤10°
Вращение	360°

05 СТАНДАРТЫ

Сертификаты CE, RoHS support, ErP, WEEE, REACH

06 РАЗМЕР / ВЕС

Размер продукта Ш x В x Г	118 x 53.4 x 48.5мм
Размер коробки Ш x В x Г	147 x 91 x 70.5мм
Вес (без упаковки)	0.2кг
Вес (с упаковкой)	0.31кг
EAN код	4948570033010

07 СОПУТСТВУЮЩАЯ ИНФОРМАЦИЯ

Сопутствующие [UC CAM120ULB-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC CAM75FS-1](#), [UC SPK01M](#)
товары



Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей. © IIYAMA CORPORATION. ALL RIGHTS RESERVED