



- INFORMATION



4K Huddle/Conference webcam with autofocus

The 13MP UC CAM80UM featuring 2D and 3D denoising technologies delivers sensational smoothness and detail, even in low light conditions. An integrated 2 microphone array detects audio from up to 4 metres away. Easy to setup and supporting 360-degree horizontal rotation with 10-degree angle adjustment, this huddle space camera supports all the leading conferencing software like Zoom, Skype, Microsoft Teams and more.



80° field of view

The field of view means the viewable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. An 80° FoV is perfect for huddle spaces which usually seat two to four people.



2D & 3D Digital Noise Reduction

Delivering high image quality, these two image denoising technologies combined ensure crisp and clear visuals for video and photos, even in low light conditions.



Auto-focus & TLens®

With the TLens® technology guaranteeing seamless transitions, your camera can quickly focus on your face, from the moment you sit in front of the lens to start the meeting.



Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.

TEHNICHESKIE-HARAKTERISTIKI

01 CAMERA

Pixels	13M
Разрешение	4K UHD
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Diagonal field of view (dFoV)	80°
Focus mode	auto
Aperture	2.2

02 AUDIO

Number of microphone arrays	2
Voice pickup distance	4m
Voice pickup angle	180°

03 CONNECTIVITY

Camera USB Type-C

04 МЕХАНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Угол наклона экрана	≤10°
Вращение	360°

05 СТАНДАРТЫ

Сертификаты CE, RoHS support, ErP, WEEE, REACH

06 PA3MEP / BEC

Размер продукта Ш х В х Г	117 х 53.5 х 48.5мм
Размер коробки Ш х В х Г	154 х 86 х 82мм
Вес (без упаковки)	0.16кг
Вес (с упаковкой)	0.31кг
EAN код	4948570033003

07 СОПУТСТВУЮЩАЯ ИНФОРМАЦИЯ

СопутствующиеUC CAM120ULB-1, UC CAM120UL-1, UC CAM180UM-1, UC CAM75FS-1, UCтоварыSPK01M, UC SPK01L



Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселов. © IIYAMA CORPORATION. ALL RIGHTS RESERVED