

UNIFIED COMMUNICATIONS



BİLGİLER

**Gizlilik kapağına sahip kompakt Full HD web kamerası**

Hem evde hem de ofiste UC CAM75FS, görüntülü toplantıların tüm avantajlarından yararlanmanızı sağlar. Entegre iki mikrofon dizisi, sesi 4 metreye kadar uzaktan algılayarak rahatsız edici arka plan gürültüsü veya bozulma olmadan yüksek kaliteli ses sunar.

Zoom, Skype, Microsoft Teams gibi tüm önde gelen konferans yazılımlarını destekler ve basit ama etkili gizlilik kapağı, kameranın sizi yalnızca siz istediğinizde görmesini garanti eder.



77° field of view

The field of view means the viewable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A below 80 degrees field of view is a perfect choice for your desktop set-up.



2D & 3D Digital Noise Reduction

Delivering high image quality, these two image denoising technologies combined ensure crisp and clear visuals for video and photos, even in low light conditions.



Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.



Privacy shutter

A manual switch shutter is one you can easily slide closed to ensure your camera can only see you when you want it to.

ÖZELLİKLER

01 KAMERA

Piksel	2M
Supported resolutions	1080p/30fps, 720p/30fps, 576p/30fps
Çapraz görüş alanı (dFoV)	77°
Odak modu	fixed
Odak mesafesi	1m
Diyafram	2

02 SES

Mikrofon dizisi sayısı	2
Ses alma mesafesi	4m
Ses alma açısı	180°

03 ÖLÇÜLER / AĞIRLIK

Ürün boyutları G x Y x D	80 x 69.5 x 38mm
Kutu boyutları G x Y x D	96 x 71 x 56mm
Ağırlık (kutu hariç)	0,05kg
Ağırlık (kutu ile birlikte)	0.1kg
EAN kodu	4948570032990

04 İLGİLİ BİLGİ

İlgili ürünler [UC CAM120ULB-1](#), [UC CAM120UL-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC SPK01M](#), [UC SPK01L](#)



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED