## іїуата



- INFORMATION



## Bluetooth Speakerphone for large meeting rooms

The omnidirectional audio pickup from up to 5 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01L the perfect choice for large meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this sleek looking speaker can be paired with up to 3 devices at the same.



### **Omnidirectional**

The UC SPK01L supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



# High-quality voice experience

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



## Easy set up

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



# Multiple device connectivity

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

— SPECIFICATION		
	•••	
	01 SPEAKER	
	Maximum sound pressure level	85dB
	Distortion	≦4%
	Signal to noise ratio	80dB
	Frequency range	150Hz ~ 16kHz
	02 MICROPHONE	

Number of microphone arrays	x6
Voice pickup range	5m (radius)
Frequency range	150Hz ~ 8kHz

#### 03 CONNECTIVITY & BUTTON OPERATIONS

USB Type C	x1 (Audio In/Out, Charge 5V/2A)
AUX	x1 (In/Out, 3.5mm, DaisyChain)
Bluetooth	4.2+EDR
Buttons	Power, Volume, Blutooth, Mute, Answer/Hang up

### 04 ACCESSORIES & BATTERY

Bluetooth receiver	yes
USB (type A to C) cable	yes
Audio cable	yes
Battery capacity	7.4V/2200mAh
Charging	wired 5V/2A, wireless 5W
Battery life on a single charge	8 hours

#### SUSTAINABILITY

05

Regulations CE, RoHS support, ErP, WEEE, REACH



Weight (without box) 0.4kg

EAN code 4948570033041





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED