



The ProLite E2472HD LED-backlit monitor is a full high definition 24" display that features all the benefits this technology affords. Slender and stylish its maximum width is 3cm, it has a narrow 1.7cm bezel, touch sensitive controls and is finished in the latest glossy-black. The high specifications on the monitor include the 5,000,000:1 ACR, fast 2ms response for excellent sharpness in high definition video and triple input connectivity (D-Sub, DVI-D, HDMI). With Eco-mode activated power consumption is down to typically 13W and less than 1W in standby.

1. DISPLAY CHARACTERISTICS

DIAGONAL	24"; 61cm
ASPECT RATIO	16 : 9
PANEL	LED-Backlit
NATIVE RESOLUTION	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
BRIGHTNESS	250 cd/m ² typical
STATIC CONTRAST	1000 : 1 typical
ADVANCED CONTRAST	5 000 000 : 1 ACR
RESPONSE TIME	2ms
VIEWING ZONE	horizontal/vertical: 170°/ 160°; right/left: 85°/ 85°; up/down: 80° / 80°
DISPLAY COLOUR	16.7 million
DISPLAY AREA H X W	298.89 x 531.36 mm; 11.8" x 20.9"
PIXEL PITCH H X V	0.277 x 0.277 mm
HORIZONTAL SYNC	31 - 83kHz

VERTICAL SYNC	56 - 75Hz
SYNCHRONIZATION	Separate sync

2. INTERFACES / CONNECTORS / CONTROLLERS

ANALOG INPUT CONNECTOR	D-Sub
DIGITAL INPUT CONNECTOR	DVI-D, HDMI
HDCP	yes
OUTPUT CONNECTOR	Audio out (only with HDMI input)

3. FEATURES

APPLE - MAC	All iiyama monitors are compatible with Apple-Macintosh computers.
PLUG & PLAY	VESA DDC2B™
CONTROLS	Via OSD in 10 languages (EN, DE, FR, ES, IT, PL, NL, Chinese, RU, JP) and 6 front controls (Power, Menu/ Select, Scroll up, Scroll down/ ECO, Exit, Auto)
USER CONTROLS	audio adjust, luminance (brightness, contrast), geometry (H. position, V. position, pixel clock, phase), colour, OSD (H. position, V. position, OSD time), language, recall, miscellaneous (sharpness, DDC/CI, display information, ACR, display mode, OD, opening logo), input select, audio (volume, mute)
ANTI-THEFT-DEVICE	Kensington-lock™ prepared
CERTIFICATES	CE, VCCI-B, TUV-Bauart
TILT ANGLE	15° up; 5° down
COLOUR	Black

4. ACCESSORIES

DRIVER	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
INCLUDED ACCESSORIES	AC adapter, power cable, D-Sub cable, DVI-D cable, stand, screw, quick start guide, safety guide

5. POWER MANAGEMENT

POWER SUPPLY	DC 12V 3A
POWER SUPPLY UNIT	external
POWER USAGE	24 W typical; max. 1 W in Power management mode
POWER MANAGEMENT	VESA DPMS, ENERGY STAR®

6. DIMENSIONS / WEIGHT

DIMENSIONS W X H X D	570 x 420 x 179 mm
WEIGHT	3.8 kg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

