

G | 4K UHD | RS232C | Slim Line | Remote | HDMI | VESA

43" profesionalni ekran za digitalno oglašavanje sa 4K UHD rezolucijom

Postavljen u tanak okvir, iiyama LE4341UHS je profesionalni digitalni displej koji nudi radno vreme 18/7 i pejzažnu orijentaciju.

4K UHD rezolucija (3840x2160) pruža izuzetne performanse boja i slike. Pomoću ugrađenog medija plejera možete da puštate svoju omiljenu muziku i prikazujete svoje najlepše video zapise, fotografije i slike direktno na ekranu.

4K

UHD rezolucija (3840x2160), poznatija kao 4K, nudi gigantsko vidljivo područje sa 4 puta više informacija i radnim prostorom od Full HD ekrana. Zbog visokog DPI-ja (tačke po inču), prikazuje neverovatno oštre i jasne slike.

Media player

Reprodukujte svoju omiljenu muziku i pokažite svoje najlepše video snimke i fotografije direktno na ekranu sa USB flash diska ili interne memorije pomoću ugrađenog medija playera.

01 KARAKTERISTIKE EKRANA

Dizajn	Tanki okvir
Dijagonala	42.5", 108cm
Panel	IPS, haze 1%
Osnovna rezolucija	3840 x 2160 (8.3 megapixel 4K UHD)
Format ekrana	16:9
Osvetljenje	350 cd/m²
Statički kontrast	1200:1
Vreme odziva (GTG)	8ms
Zona gledanja	horizontalno/vertikalno: horizontal°/vertical 178°, desno/levo: 0°/0°, gore/dole: 0°/0°
Podržane boje	1.07B 10bit (8bit + Hi-FRC) (NTSC 72%)
Horizontalna sinhronizacija	30 - 83KHz
Vidljiva površina Š x V	941.2 x 529.4mm, 37.1 x 20.8"
Razmak piksela	0.245mm
Boja okvra	crna, sjajna

02 KONEKTORI / KONTROLE

Ulaz analognog signala	VGA x1 (max. 1920x1080 @60Hz)
Ulaz digitalnog signala	HDMI x3 (max. 3840x2160 @60Hz)
Audio ulaz	Mini konektor x1
Kontrolni ulaz	RS-232c x1 RJ45 (LAN) x1 IR x1
Audio izlaz	RCA (L/R) x1 Zvučnici 2 x 10W
Monitor kontrolni izlaz	RS-232c x1 IC loop x1
HDCP	2.2
USB portovi	x1 (2.0, FW update support)

03 KARAKTERISTIKE

Maksimalno neprekidno radno vreme	18/7
Protiv zadržavanja slike	da
Reprodukcija medija	da
Kućište (okvir)	plastika

04 OPŠTE

OSD jezici	EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL
Kontrolni tasteri	Napajanje, Isključivanje zvuka, Ulaz, Plus, Minus, Gore, Dole, Meni
Korisničke kontrole	slika (format slike, temp. boje, smanjenje šuma, dinamički kontrast, gama, osvetljenost, nivo crne boje, boja, kontrast, nijansa, oštrina, RGB opseg, resetovanje), zvuk (visoki tonovi, bas, balans, zvučnik, audio izlaz, resetovanje), opšta podešavanja 1 (jezici menija, sat, raspored, HDMI CEC veza, HDMI režimi, podešavanje komunikacije), ekran (automatsko podešavanje, sat, faza, H. pozicija, V. pozicija, resetovanje), opšta podešavanja 2 (automatsko napajanje isključeno, stanje pripravnosti mreže, upravljanje napajanjem, automatsko otkrivanje signala, automatska reprodukcija, lokalno KB zaključavanje, RC zaključavanje, ID monitora, LED, pomeranje piksela, informacije, fabrička podešavanja)

05 MEHANIČKI

Orijentacija	pejzaž
Dizajniran bez ventilatora	da
VESA montiranje	400 x 400mm
Opseg radne temperature	0°C - 40°C
Temperatura skladištenja	- 20°C - 60°C
MTBF - Prosecno vreme izmedju kvarova	50000 sati (izuzimajući pozadinsko osvetljenje)

06 UKLJUČENI DODACI

Kablovi	Strujni kabl, HDMI, RS-232c
Upustva	kratko uputstvo, bezbednosni vodič
Daljinski upravljač	da (baterije uključene)

07 UPRAVLJANJE NAPAJANJEM

Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W iskljucen

08 ODRŽIVOST

Propisi	CB, CE, TÜV-Bauart, EAC, RoHS podrška, ErP, WEEE, REACH
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	G
REACH SVHC	iznad 0.1%: Olova

09 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	972 x 560 x 67.5mm
Dimenzije kutije Š x V x D	1070 x 690 x 139mm
Težina (bez kutije)	8.8kg
Težina (sa kutijom)	12.3kg
EAN kod	4948570120932



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED