UNIFIED COMMUNICATIONS

INFORMACIJE

Elegantna i diskretna profesionalna 4K veb kamera sa ugrađenim mikrofonom, 5k digitalnim zumom, vidnim poljem od 120° (FoV) i automatskim praćenjem

Ova elegantna, profesionalna 4K veb kamera sa 5k digitalnim zumom i ugrađenim mikrofonom podići će vaše video konferencije na novi nivo. Sa vidnim poljem od 120° i zumom od 5k, UC-CAM10PRO-1 pruža senzacionalnu, glatku i detaljnu sliku. Veb kamera ima dva ugrađena mikrofona koji detektuju zvuk sa udaljenosti do 4 metra, tako da možete biti sigurni da će se svi čuti tokom sastanaka. Ova kamera kompaktne veličine sa poklopcem za privatnost savršeno se uklapa u svaki prostor - bilo da je u pitanju mali prostor za druženje ili sala za sastanke. Sa funkcijom podešavanja nagiba od 14°, kamera se može prilagoditi vašim potrebama i prilagoditi vašem individualnom prostoru.

120° vidno polje

Vidno polje označava područje koje se može videti kroz objektiv kamere. To direktno previđa koliko će vašeg prostora za sastanke biti vidljivo učesnicima koji se pridružuju na daljinu. FoV od 120 stepeni je pravo rešenje za većinu standardnih prostora za sastanke.

2D i 3D digitalna redukcija šuma

Pružajući visok kvalitet slike, ove dve tehnologije za smanjenje šuma u kombinaciji obezbeđuju oštre i jasne slike za video i fotografije.



Auto kadriranje

Sa inteligentnom detekcijom lica i lokalizacijom glasa, kamera prati ko god govori i glatko se prebacuje između prezentatora automatski prilagođavajući se lokaciji i količini učesnika. Ne samo da prepoznaje i zumira učesnike sastanka, već i prati govornike dok se kreću po prostoriji.

Jasan, oštar i prirodan zvuk

Sa naprednim algoritamom za smanjenje šuma, integrisani mikrofonski niz od 2 elementa detektuje zvuk sa udaljenosti do 4 metra, isporučujući zvuk visokog kvaliteta bez bilo kakve dosadne pozadinske buke ili izobličenja.

SPECIFIKACIJA

01 KAMERA

Pikseli	8,46M
Osnovna rezolucija	4K UHD
Podržavne rezolucije	2160p/30fps, 1440p/30fps, 1080p/30fps
Dijagonalno vidno polje (dFoV)	120°
Režim fokusa	fiksno
Udaljenost fokusa	8m
Otvor blende	2.5
Zum	5x digitalni zum
Balans bele boje	da
Exspozicija	da
Kompenzacija pozadinskog osvetljenja	da
Kadriranje	da

02 AUDIO

Broj nizova mikrofona	2
Hvatanja udaljenog glasa	4m
Ugao hvatanja glasa	180°
Redukcija buke	da
Automatska kontrola pojačanja	da

03 KONEKCIJA

Kamera	USB Tip-C
Host	USB v.3.0

04 MIKROFON

Broj nizova mikrofona	x2
Opseg podizanja glasa	4m (radius)

05 KONEKCIJE I UPOTREBA TASTERA

USB tip C	x1

06 MEHANIČKI

Ugao nagiba	≤14°
Rotacija	360°
Poklopac kamere	yes

07 UKLJUČENI DODACI

Kablovi	USB 2.0 (tip A do C)
Poklopac za kameru	da
Daljinski upravljač	da (baterije uključene)
Adapter za napajanje	da

08 ODRŽIVOST

Propisi	CE, RoHS podrška, ErP, WEEE, REACH, UKCA

09 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	80 x 75 x 53mm
Dimenzije kutije Š x V x D	162 x 124 x 90mm
Težina (bez kutije)	0.21kg
Težina (sa kutijom)	0.5kg
EAN kod	4948570033140

10 POVEZANE INFORMACIJE

Povezani prizvodi	UC CAM120ULB-1, UC CAM180UM-1, UC CAM80UM-1, UC SPK01M

GALERIJA



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**