

UNIFIED COMMUNICATIONS



BİLGİLER





### 120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.



### 2D & 3D Digital Noise Reduction



### Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.



### Clear, crisp and natural audio

Featuring an advanced noise reduction algorithm, the integrated 2-element mic array detects audio from up to 4 metres away, delivering high quality audio free from any annoying background noise or distortion.

## ÖZELLİKLER

### 01 KAMERA

Piksel	8,46M
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Çapraz görüş alanı (dFoV)	120°
Odak modu	fixed
Odak mesafesi	8m
Diyafram	2.5
Zoom	5x digital zoom

### 02 SES

Mikrofon dizisi sayısı	2
Ses alma mesafesi	4m
Ses alma açısı	180°

### 03 BAĞLANTI

Host USB v.3.0

### 04 MIKROFON

Number of microphone arrays	x2
Voice pickup range	4m (radius)

### 05 CONNECTIVITY & BUTTON OPERATIONS

USB Type C x1

### 06 MEKANİK

Eğim açısı	≤14°
Döndürme	360°
Gizlilik deklanşörü	yes

### 07 ÖLÇÜLER / AĞIRLIK

Ürün boyutları G x Y x D	80 x 75 x 53mm
Kutu boyutları G x Y x D	162 x 124 x 90mm
Ağırlık (kutu hariç)	0.21kg

Ağırlık (kutu ile birlikte)

0.5kg

EAN kodu 4948570033140

08

## İLGİLİ BİLGİ

İlgili ürünler [UC CAM120ULB-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC SPK01M](#)



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IYAMA CORPORATION. ALL RIGHTS RESERVED