UC-CAM10PRO-MA1 preliminary

UNIFIED COMMUNICATIONS

BİLGİLER

120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.

2D & 3D Digital Noise Reduction



Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.

Clear, Crisp and Natural Audio

Featuring an advanced noise reduction algorithm, the integrated 8-element mic array detects audio from up to 8 metres away, delivering high quality audio free from any annoying background noise or distortion.

ÖZELLIKLER

01 KAMERA

Piksel	8.46M
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Çapraz görüş alanı (dFoV)	120°
Odak modu	fixed
Odak mesafesi	8m
Diyafram	2.5
Zoom	5x digital zoom
AutoFraming	Evet
Kamera konumu ön ayarı sayısı	1

02 SES

Mikrofon dizisi sayısı	8
Ses alma mesafesi	8m
Ses alma açısı	180°

03 BAĞLANTI

Host	USB v.3.0

04 MIKROFON

Number of microphone arrays	x8
Voice pickup range	8m (radius)

05 CONNECTIVITY & BUTTON OPERATIONS

USB Type C	x1

06 MEKANİK

Eğim açısı	≤15°
Döndürme	360°
Gizlilik deklanşörü	yes

07 ÖLÇÜLER / AĞIRLIK

Ürün boyutları G x Y x D	300. x 85 x 100mm

Kutu boyutları G x Y x D	300 x 84 x 100mm
Ağırlık (kutu hariç)	0.346kg
Ağırlık (kutu ile birlikte)	1kg
EAN kodu	4948570033157

08 İLGİLİ BİLGİ

İlgili ürünler	UC CAM120ULB-1, UC CAM180UM-1, UC CAM80UM-1, UC CAM75FS-1, UC SPK01M

GALERİ

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**