75" Interaktivni 4K UHD LCD dodirni ekran sa integrisanim softverom za beleške

Pojednostavili smo saradnju između obrazovanje i preduzeća. TE7512MIS-B1AG iiyama monitor nas inspiriše u sve mogućnosti i svim fazama od obrazovanja, pokretanje i vodjenja velikih preduzeća. Sa našim hibridnim interaktivnim rešenjem, možete glatko da beležite u 4K rezoluciji i da kontrolišete bilo koji sadržaj na ekranu iz bilo kog izvora.

Ovaj PureTouch-IR ekran osetljiv na dodir sa 40 tačaka sa iiWare 10 (Android 11 OS) sadrži Note, pretraživač, Cloud Drive i opciju za učitavanje relevantnih aplikacija koje su vam potrebne za vašu organizaciju. Dolazi sa olovkama za dodir sa dvostrukom funkcijom i lako možete da sačuvate svoje beleške i sadržaj na ekranu direktno na USB uređaj, internu memoriju od 32 GB ili odabrani klaud disk. Uključujući dodatnu USB-C vezu, ekran podržava najnoviji video, audio i Touch signal preko jednog porta i čak puni vaš uređaj snagom od 65 W.

Sa 4K UHD rezolucijom (3840x2160) i osvetljenošću od 400cd/m2, ovaj IPS LCD ekran od 75” pruža živopisne, detaljne i visokokvalitetne slike sa bilo kog mesta u učionici ili sali za sastanke. Premaz protiv odsjaja drastično smanjuje refleksiju ambijenta u okruženjima visoke osvetljenosti bez ugrožavanja oštrine i jasnoće slike.

Možete biti sigurni da bez obzira na vašu težnju za interaktivnost, iiyama ima pojednostavljeno rešenje samo za vas. Sa novim 4K interfejsom sa korisničkim profilima za jednostavnu prijavu i pristup vašem sopstvenom meniju po meri i Cloud diskovima, TE7512MIS-B1AG postaje visoko personalizovan uređaj u užurbanom hibridnom okruženju za više korisnika.

Delite, strimujte i uređujte sadržaj sa bilo kog uređaja direktno na ekranu i transformišite sastanke ili lekcije svog tima u laku, brzu i besprekornu interaktivnu sesiju sa uključenim WiFi modulom (OWM002), aplikacijom iiyama Share i EShare

PureTouch-IR+

PureTouch-IR+ kompanije iiyama pruža tačnost dodira od 1 mm za najglatkiju i najbržu belešku.

01 KARAKTERISTIKE EKRANA

Dizajn	Tanki okvir
Dijagonala	75", 189.3cm
Panel	VA
Dodirno staklo	Anti-Gloss treatment, Anti-Glare glass, Matt polished surface, Ultra smooth writing, bez vazdupnih džepova
Osnovna rezolucija	3840 x 2160 (8.3 megapixel 4K UHD)
Format ekrana	16:9
Osvetljenje	435 cd/m²
Propusnost svetla	92%
Statički kontrast	5000:1
Dinamički kontrast	5000:1
Vreme odziva (GTG)	8ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	1.07B 10bit (8bit + Hi-FRC) (NTSC 72%)
Horizontalna sinhronizacija	30 - 135KHz
Vidljiva površina Š x V	1650 x 928mm, 65 x 36.5"
Širina okvira (stranice, vrh, dno)	16.5mm, 16.5mm, 41mm
Razmak piksela	0.430mm
Boja okvra	crna, mat

02 TOUCH

Touch tehnologija	PureTouch-IR+
Tačke dodira	50, 10pt writing (HID, samo uz podržani OS)
Preciznost dodira	+- 1mm
Način dodira	olovka, prst, rukavica
Interfejs dodira	USB
Podržani operativni sistemi	Svi iiyama monitori su Plug & Play kompatibilni sa Windows Linux operativnim sistemima. Detalje o podržanom OS-u za modele osetljive na dodir potražite u odjeljku za preuzimanje u uputstvima za instalaciju drajvera.
Odbijanje dlana	da

03 KONEKTORI / KONTROLE

Ulaz digitalnog signala	HDMI x4 (2.0, max. 3840x2160 @60Hz, YUV420/ YUV444/ RGB444) DisplayPort x1 (2.1, max. 3840x2160 @30Hz) USB-C x2 (v.3.2 (Gen 1, 5Gbit), 3840x2160 @60Hz, RGB444 | DP 1.2 Alt mode, Touch, 1x front: 100W PD , 1x back: 15W PD)
Audio ulaz	Mini konektor x1
Kontrolni ulaz	RS-232c x1 (DSUB 9pin) RJ45 (LAN) x1 (LAN Control) IR x1
Digitalni izlaz signala	HDMI x1 USB-C x1 (v.3.2 (Gen 1, 5Gbit), 3840x2160 @60Hz (DP 1.2 Alt mode, Touch, 5W PD, MSD (Multi-Screen Display))
Audio izlaz	S/PDIF (Optički) x1 Mini konektor x1 Zvučnici 2 x 18W (Facing up), 2x 8W
HDCP	HDMI: 2.3 + 1.4, DP: 2.3 + 1.3 USB-C: 2.3 + 1.3

USB portovi	x6 (media playback / peripherals / storage – front side: 2x v.3.2 (Gen 1, 5Gbit), 1x USB-C v.3.2 (Gen 1, 5Gbit, 100W PD), back side: 2x v.3.2 (Gen 1, 5Gbit), 1x USB-C v.3.2 (Gen 1, 5Gbit, 15W PD))
RJ45 (LAN)	x2 (Automatsko prebacivanje na PC i Android, 1000 MB)
Mikrofon	8-Array (8m voice pick-up, Front facing)

04 KARAKTERISTIKE

Integrisani softver	iiWare 11 (Android OS 13) koji sadrži iiyama DMS, Note, web pregledač, menadžer datoteka, cloude diskove, WPS office, iiyama Share i EShare za bežičnu vezu sa Windovs / iOS / Android uređajima
WiFi	da (WiFi 6 Module OWM002 - Dual WiFi Bandwidth: 2.4GHz/5GHz, WiFi Standard: IIEEE 802.11 a/b/g/n/ac/ax, Bluetooth Support: 2.1+EDR/ 3.0/ 4.x/ 5.0)
Hardver	CPU: A76*4+A55*4(2.4GHz), GPU: Mali G610 MC4, RAM: 8GB, ROM: 64GB
Dodatno	WiFi 6 Modul (OWM002), Slot for optional OPS Slot PC, 4x Touch pen
Kiosk mod	da
Maksimalno neprekidno radno vreme	24/7
Reprodukcija medija	da
Debljina stakla	3mm
Tvrdoća stakla	7H
Kućište (okvir)	metal
Zaključavanje OSD tastera	da

05 OPŠTE

OSD jezici	EN, DE, FR, ES, IT, RU, CZ, NL, PL, SV, FI, DA, NB
Redukcija plavog svetla	da
Plug&Play	DDC2B
Garancija	5 godina (za detalje i zemlje koje ispunjavaju uslove potražite odeljak Garancija na našoj web stranici)

06 MEHANIČKI

Orijentacija	pejzaž
Dizajniran bez ventilatora	da
VESA montiranje	800 x 400mm
Opseg radne temperature	0°C - 40°C
Temperatura skladištenja	- 20°C - 60°C
MTBF - Prosecno vreme izmedju kvarova	50.000 sati (izuzimajući pozadinsko osvetljenje)

07 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI
Olovka za dodir	x4
Upustva	kratko uputstvo, bezbednosni vodič
Ostalo	WiFi 6 modul (OVM002), nosač za NUC, nosač za web kameru
Daljinski upravljač	da (baterije uključene)

08 UPRAVLJANJE NAPAJANJEM

Napajanje	interna

Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W iskljucen

09 ODRŽIVOST

Propisi	CB, CE, TÜV-Bauart, EAC, RoHS podrška, ErP, WEEE, REACH (RoHS)
REACH SVHC	iznad 0.1%: Olova

10 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	1709 x 1031 x 86mm
Dimenzije kutije Š x V x D	1863 x 1148 x 225mm
Težina (bez kutije)	51.5kg
Težina (sa kutijom)	60.8kg
EAN kod	4948570122035



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED