iiyama DMS | PureTouch-IR+ | OPS PC Slot | USB-C | 4K UHD | Note | 50 | RS232C | Media Player | AG Coating | DISPLAY PORT | Remote | HDMI | VESA

65" Interaktivni 4K UHD LCD dodirni ekran sa integrisanim softverom za beleške

Podelite svoju viziju sa ProLite TE6514MIS-B1AG; savršenim rešenjem za obrazovanje i korporativnu upotrebu. 65" PureTouch-IR+ dodirni ekran sa 50 tačaka sa iiWare 11 (Android OS 13) koji sadrži program za beleške, web browser, menadžer datoteka, cloude diskove, WPS office i ScreenSharePro. Dolazi sa olovkama sa dvostrukim dodirom, koje korisnicima omogućavaju lagano beleženje u 4K rezoluciji na datotekama i sadržajima na ekranu, koji se mogu sačuvati direktno na USB uređaj, internu memoriju od 32GB ili na povezani uređaj u cloude-u. Ekran podržava ponavljanje prezentacija, video zapisa visoke rezolucije i gotovo bilo koju drugu vrstu sadržaja.

Visoko kvalitetni komercijalni VA LCD ekran sa 4K UHD rezolucijom (3840x2160), 400cd/m² i kontrastnim odnosom od 4000:1, pruža živopisne, detaljne i visokokvalitetne slike bilo gde, u učionici ili sobi za sastanke. Premaz protiv odsjaja drastično smanjuje ambijentalnu refleksiju u okruženjima visoke osvetljenosti, a da ne ugrozi oštrinu i jasnoću slike. Ekran ima 24/7 non-stop vreme rada i opremljen je metalnim okvirom, kaljenim staklom debljine 3mm, kako bi se osigurala dugotrajna izdržljivost u okruženjima česte upotrebe, poput učionica ili sala za sastanke.

Delite, strimujte i uređujte sadržaj sa bilo kojeg uređaja direktno na ekranu i transformišite sastanke ili predavanja svog tima u laku, brzu i nesmetanu interaktivnu sesiju sa uključenim WiFi modulom (OWM002), aplikacijom iiyama Share i EShare

PureTouch-IR+

PureTouch-IR+ kompanije iiyama pruža tačnost dodira od 1 mm za najglatkiju i najbržu belešku.

01 KARAKTERISTIKE EKRANA

Dizajn	Tanki okvir
Dijagonala	65", 163.9cm
Panel	VA, haze 25%
Dodirno staklo	Anti-Gloss treatment, Anti-Glare glass, Matt polished surface, Ultra smooth writing, bez vazdupnih džepova
Osnovna rezolucija	3840 x 2160 (8.3 megapixel 4K UHD)
Format ekrana	16:9
Osvetljenje	435 cd/m²
Propusnost svetla	92%
Statički kontrast	4000:1
Dinamički kontrast	5000:1
Vreme odziva (GTG)	6.5ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	1.07B 10bit (8bit + Hi-FRC) (NTSC 72%)
Horizontalna sinhronizacija	30 - 135KHz
Vidljiva površina Š x V	1429 x 804mm, 56.3 x 31.7"
Širina okvira (stranice, vrh, dno)	16.5mm, 16.5mm, 41mm
Razmak piksela	0.372mm
Boja okvra	crna, mat

02 TOUCH

Touch tehnologija	PureTouch-IR+
Tačke dodira	50, 10pt writing (HID, samo uz podržani OS)
Preciznost dodira	+- 1mm
Način dodira	olovka, prst, rukavica
Interfejs dodira	USB
Podržani operativni sistemi	Svi iiyama monitori su Plug & Play kompatibilni sa Windows Linux operativnim sistemima. Detalje o podržanom OS-u za modele osetljive na dodir potražite u odjeljku za preuzimanje u uputstvima za instalaciju drajvera.
Odbijanje dlana	da

03 KONEKTORI / KONTROLE

Ulaz digitalnog signala	HDMI x4 (2.0, max. 3840x2160 @60Hz, YUV420/ YUV444/ RGB444) DisplayPort x1 (2.1, max. 3840x2160 @30Hz) USB-C x2 (v.3.2 (Gen 1, 5Gbit) 3840x2160 @60Hz, RGB444 | DP 1.2 Alt mode, Touch, 1x front: 100W PD , 1x back: 15W PD)
Audio ulaz	Mini konektor x1
Kontrolni ulaz	RS-232c x1 (DSUB 9pin) RJ45 (LAN) x1 (LAN Control) IR x1
Digitalni izlaz signala	HDMI x1 (2.0, max. 3840x2160 @60Hz, MSD (Multi-Screen Display)) USB-C x1
Audio izlaz	S/PDIF (Optički) x1 Mini konektor x1 Zvučnici 2 x 18W (Facing up), 2x 8W (Front facing)
HDCP	HDMI: 2.3 + 1.4, DP: 2.3 + 1.3, USB-C: 2.3 + 1.3
USB portovi	x6 (media playback / peripherals / storage – front side: 2x v.3.2 (Gen 1, 5Gbit), 1x USB-C v.3.2 (Gen 1, 5Gbit, 100W PD), back side: 2x v.3.2 (Gen 1, 5Gbit), 1x USB-C v.3.2 (Gen 1, 5Gbit, 15W PD))

RJ45 (LAN)	x2 (Automatsko prebacivanje na PC i Android, 1000 MB)
Mikrofon	8-Array (8m voice pick-up, Front facing)

04 KARAKTERISTIKE

Integrisani softver	iiWare 11 (Android OS 13) koji iiyama DMS, sadrži Note, web pregledač, menadžer datoteka, cloude diskove, WPS office, BytelloShare i EShare za bežičnu vezu sa Windovs / iOS / Android uređajima
WiFi	da (WiFi 6 Module OWM002 - Dual WiFi Bandwidth: 2.4GHz/5GHz, WiFi Standard: IIEEE 802.11 a/b/g/n/ac/ax, Bluetooth Support: 2.1+EDR/ 3.0/ 4.x/ 5.0)
Hardver	CPU: A76*4+A55*4(2.4GHz), GPU: Mali G610 MC4, RAM: 8GB, ROM: 64GB
Dodatno	WiFi 6 Modul (OWM002), Slot for optional OPS Slot PC, 4x Touch pen
Kiosk mod	da
Maksimalno neprekidno radno vreme	24/7
Reprodukcija medija	da
Debljina stakla	3mm
Tvrdoća stakla	7H
Kućište (okvir)	metal
Zaključavanje OSD tastera	da

05 OPŠTE

OSD jezici	EN, DE, FR, ES, IT, RU, CZ, NL, PL, CAT, SV, FI, DA, NB
Kontrolni tasteri	Power, Power Indicator, Remote Sensor, Light Sensor, USB-C Connector (3.1)
Redukcija plavog svetla	da
Plug&Play	DDC2B
Garancija	5 godina (za detalje i zemlje koje ispunjavaju uslove potražite odeljak Garancija na našoj web stranici)

06 MEHANIČKI

Orijentacija	pejzaž
Dizajniran bez ventilatora	da
VESA montiranje	600 x 400mm
Opseg radne temperature	0°C - 40°C
Temperatura skladištenja	- 20°C - 60°C
MTBF - Prosecno vreme izmedju kvarova	50.000 sati (izuzimajući pozadinsko osvetljenje)

07 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI
Olovka za dodir	x4
Upustva	kratko uputstvo, bezbednosni vodič
Daljinski upravljač	da (baterije uključene)

08 UPRAVLJANJE NAPAJANJEM

Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W iskljucen

09 ODRŽIVOST

Propisi	CB, CE, TÜV-Bauart, EAC, RoHS podrška, ErP, WEEE, REACH (RoHS)
REACH SVHC	iznad 0.1%: Olova

10 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	1488 x 908 x 86mm
Dimenzije kutije Š x V x D	1628 x 1005 x 208mm
Težina (bez kutije)	39kg
Težina (sa kutijom)	48.3kg
EAN kod	4948570122028



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED