

## IFP INTERACTIVE DISPLAYS





## INFORMATION

## 105" Ultra-wide Interactive 5K UHD display with 21:9 panoramic view



- The TE10518UWI-B1AG is a revolutionary 105" 5K UHD Interactive Touchscreen that brings a new level of collaboration and engagement to your workspace. Boasting cutting-edge technology and a host of impressive features and functionalities, this interactive display is designed to transform the way you work, communicate, and share ideas. Whether it's for boardrooms, classrooms, or collaborative meeting spaces, this 105" 21:9 Ultra-Wide interactive touchscreen is the ultimate tool to foster creativity, productivity, and seamless communication.




## Microsoft Teams Front Row

Take your collaboration to the next level with the integration of Microsoft Teams Front Row. This feature allows you to seamlessly host or join virtual meetings and video conferences using the interactive touchscreen as your central communication hub.

## 21:9 Ultra-Wide Screen

With an ultra-wide aspect ratio, this interactive touchscreen provides an expansive canvas to accommodate multiple content windows side-by-side, enhancing multitasking capabilities. The 21:9 Ultra Wide format is also the perfect optimisation for Microsoft Teams Front Row delivering an exceptional experience and meeting room equity for all attendees.



## 5K - 11 Mega Pixels

Experience stunning visuals with the 5K UHD resolution, offering crisp and clear images for a truly immersive viewing experience.



## PURETOUCH-IR+

The state-of-the-art PureTouch-IR+ technology ensures accurate and precise touch responses, enabling effortless interaction and annotation.

## SPECIFICATION

### 01 DISPLAY CHARACTERISTICS

Design	Thin bezel
Diagonal	104.6", 265.7cm
Panel	VA
Touch Glass	AG coated glass, Anti-Gloss finish with excellent smooth writing (Anti-glare glass with Matt polish finish)
Native resolution	5120 x 2160 (14.75 megapixel, 5K UHD)
Aspect ratio	21:9
Panel brightness	450 cd/m <sup>2</sup>
Light transmittance	92%
Static contrast	4000:1
Dynamic contrast	5000:1
Response time (GTG)	6.5ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (NTSC 90%)
Horizontal Sync	30 - 135kHz
Viewable area W x H	2450 x 1033.6mm, 96.5 x 40.7"
Pixel pitch	0.479mm
Bezel colour and finish	black, matte

### 02 TOUCH

Touch technology	PureTouch-IR <sup>+</sup>
Touch points	40, 32pt writing (HID, only with supported OS)
Touch accuracy	+/- 1mm
Touch method	stylus, finger, glove
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Palm rejection	yes

### 03 INTERFACES / CONNECTORS / CONTROLS

Digital signal input	HDMI x4 (1x 2.1, max. 5120x 2160 @60Hz; 3x 2.0, max. 3840x2160 @60Hz, YUV444) DisplayPort x1 (1.4, max. 5120x 2160 @60Hz) USB-C x2 (3.2 Gen 1, 3840x2160 @60Hz, DP Alt mode 1.2, Touch, front: 15W PD, back: 100W PD)
Audio input	Mini jack x1
Monitor control input	RS-232c x1
Digital signal output	HDMI x1 (3840x2160 @60Hz, YUV/RGB444) USB-C x1 (3.2 Gen 1, 3840x2160 @60Hz (DP 1.2 Alt mode, Touch, 5W PD, MSD (Multi-Screen Display)))

<b>Audio output</b>	S/PDIF (Optical) x1 Mini jack x1 Speakers 2 x 16W (Front + 16W Subwoofer)
<b>HDCP</b>	HDMI, DP & USB-C: 2.3
<b>USB ports</b>	x8 (media playback / peripherals / storage – front: 2x 3.2 (Gen 1, 5Gbit), 1x USB-C 3.2 (Gen 1, 15W PD), back side: 2x 3.2 (Gen 1, 5Gbit), 1x USB-C 3.2 (Gen 1, 100W PD), top side: 2x 3.2 (Gen 1, 5Gbit))
<b>RJ45 (LAN)</b>	x2 (IN/OUT, Auto switch for PC & Android, 1000MB)
<b>Microphone</b>	8-Array (8m voice pick-up, Front facing)

## 04 FEATURES

<b>Integrated software</b>	iiWare 11 (Android 13 OS) featuring iiyama DMS, Note, web browser, file manager, cloud drives, WPS office, iiyama Share and EShare for wireless connection with Windows/iOS/Android devices
<b>WiFi</b>	yes (WiFi 6 Module OWM002 - Dual WiFi Bandwidth: 2.4GHz/5GHz, WiFi Standard: IEEE 802.11 a/b/g/n/ac/ax, Bluetooth Support: 2.1+EDR/ 3.0/ 4.x/ 5.0)
<b>Hardware</b>	CPU: A311D2 Quad core A76+A55, GPU: Mali G610, RAM: 8GB, ROM: 64GB
<b>Extra</b>	WiFi 6 Module (OWM002), Slot for optional OPS Slot PC, 4x Touch pen
<b>Kiosk mode</b>	yes
<b>Max. non-stop operating time</b>	16/7
<b>Anti image retention</b>	yes
<b>Media playback</b>	yes
<b>Glass thickness</b>	3mm
<b>Glass hardness</b>	7H
<b>Housing (bezel)</b>	metal
<b>OSD key lock</b>	yes

## 05 GENERAL

<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, CZ, NL, PL, CAT, SV, FI, DA, NB
<b>Control buttons</b>	Power, Power Indicator, Remote Sensor, Ambient Light Sensor, USB-C Connector (3.2), USB Connector (3.2), Microphone Indicator
<b>User controls</b>	common settings (input, volume, backlight), audio settings (volume, bass, treble, balance, sound mode, mute), screen settings (pixel shift, eye care, auto light, ECO, ECR, auto colour temp.), display settings (brightness, contrast, hue, sharpness, display mode, colour temp.), settings (wireless & networks, personal, input & output, application, system)
<b>Blue light reducer</b>	yes
<b>Plug&amp;Play</b>	DDC2B

## 06 MECHANICAL

<b>Orientation</b>	landscape
<b>Fanless design</b>	yes
<b>VESA mounting</b>	1000 x 400mm
<b>Operation temperature range</b>	0°C - 40°C
<b>Storage temperature</b>	- 20°C - 60°C

range

MTBF	50.000 hours (excluding backlight)
------	------------------------------------

## 07 ACCESSORIES INCLUDED

Cables	power, USB, HDMI
--------	------------------

Touch pen	x4 (Dual function tips, Anti-Bacterial)
-----------	---

Guides	quick start guide, safety guide
--------	---------------------------------

Other	WiFi Module (OWM002), Wall Mounting Bracket (VESA 1000x400mm), Mounting bracket for NUC, Mounting bracket for webcam
-------	--

Remote control	yes (batteries included)
----------------	--------------------------

## 08 POWER MANAGEMENT

Power supply unit	internal
-------------------	----------

Power supply	AC 100 - 240V, 50/60Hz
--------------	------------------------

Power usage	282W typical, 0.5W stand by, 0.3W off mode
-------------	--

## 09 SUSTAINABILITY

Regulations	CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH (RoHS)
-------------	--

REACH SVHC	above 0.1%: Lead
------------	------------------

## 10 DIMENSIONS / WEIGHT


Product dimensions W x H x D	2507.2 x 1130.1 x 103mm
---------------------------------	-------------------------

Box dimensions W x H x D	2668 x 1305 x 280mm
-----------------------------	---------------------

Weight (without box)	91.4kg
----------------------	--------

Weight (with box)	119.5kg
-------------------	---------

EAN code	4948570122011
----------	---------------



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED