



## Wireless AC1200 Dual-Band MU-MIMO mini USB 3.0 Adapter

Upgrade your wireless device to dual-band 802.11ac with the fastest possible USB 3.0 connectivity for blistering WiFi speeds on the interference free 5GHz frequency band. The Edimax EW-7822UTC is the next generation of WiFi adapter, compatible with the draft 802.11ac standard and delivering speeds of up to 867Mbps at 5GHz - almost three times as fast as 802.11n.

Upgrade the professional large format displays of the TF39AS SERIES to super high speed 802.11ac WiFi and enjoy streaming video and data.

Supporting MU-MIMO, the EW-7822UTC allows greater WiFi efficiency and has a one-click WiFi Protected Setup (WPS) button to help you set up and activate a secure wireless network in a snap.

For more details, please click [HERE](#)

### 01 DEVICE

**WiFi** AC1200 WiFi 5, Max. data transfer rates up to 867Mbps (5GHz) and 300Mbps (2.4GHz)

**Operating system** Windows 7/8/8.1/10, Mac OS 10.9 - 10.15 and Linux Kernel: 2.6.24 ~ 4.15

### 02 TECHNICAL SPECIFICATION

**WiFi standard** 2.4GHz: IEEE 802.11b/g/n, 5GHz: IEEE 802.11ac/a/n

### 03 DIMENSIONS / WEIGHT

**Product dimensions L x W x H** 8 x 16 x 34mm

**Weight (without box)** 0.04kg

**EAN code** 4717964701619

### 04 ENVIRONMENTAL CONDITIONS

**Operation temperature range** 0°C - 40°C

**Operation humidity** 0% - 90%

**Storage temperature range** - 20°C - 60°C

**Storage humidity** 0% - 95%

**Related products**

[ProLite TF3239MSC-B1AG](#), [ProLite TF4339MSC-B1AG](#), [ProLite TF6539UHSC-B1AG](#), [ProLite TF5039AS-B1AG](#), [ProLite TF5539AS-B1AG](#)

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IYAMA CORPORATION. ALL RIGHTS RESERVED