



34” curved ultra-wide screen with 15cm height adjustable stand


The ProLite XCB3493WQSU is a 34-inch curved monitor with a VA panel, delivering high contrast, deep blacks, and wide viewing angles for consistent image quality from any perspective. UWQHD (Ultra-Wide QHD) resolution provides an ultra-wide (21:9) viewable area. The large amount of screen space and good pixel density make it very suitable for those who want to use side-by-side applications, watch widescreen content or enhance their gaming experience.

For added comfort and flexibility, the 15cm height-adjustable stand allows you to adjust the screen position to your preference. Additionally, flicker-free technology and a blue light reducer function reduces eye fatigue.



VA

VA panel technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



CURVED DESIGN 1500R

The 1500R curvature of the screen reduces the strain on your eyes while providing a realistic viewing experience. It allows a comprehensive and more natural viewing angle than you'll have with flat monitors lined up side by side. The result is a more immersive experience which boosts productivity and focus whether it be for work, gaming, entertainment, editing or more.

01 DISPLAY CHARACTERISTICS

| | |
|-----------------------------|---|
| Design | curved |
| Diagonal | 34", 86.7cm |
| Panel | VA panel, matte finish |
| Curved | 1500R |
| Native resolution | 3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort) |
| Aspect ratio | 21:9 |
| Panel brightness | 350 cd/m ² |
| Static contrast | 3000:1 |
| Advanced contrast | 80M:1 |
| Response time (MPRT) | 0.4ms |
| Viewing zone | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support | 16.7mln (sRGB: 99%; NTSC: 93%) |
| Horizontal Sync | 30 - 180kHz |
| Viewable area W x H | 797.2 x 333.7mm, 31.3 x 13.1" |
| Pixel pitch | 0.232mm |
| Colour | matte, black |

02 INTERFACES / CONNECTORS / CONTROLS

| | |
|----------------------------|--|
| Signal input | HDMI x2 (1x v.2.0 and 1x v. 1.4, 3440x1440 @100Hz, 2560x1440 @120Hz) DisplayPort x1 (v.1.4, 3440 x 1440 @120Hz) |
| USB HUB | x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W)) |
| HDCP | yes |
| Headphone connector | yes |

03 FEATURES

| | |
|------------------------------|---|
| Blue light reducer | yes |
| Flicker free | yes |
| Adaptive Sync support | FreeSync Premium - HDMI: 2560 x 1440 @48-120Hz, DP: 3440 x 1440 @48-120Hz |
| Extra | i-Style Colour |
| OSD languages | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL |
| Control buttons | Joystick: Power/ Menu (Centre), Forward/ Signal Select, Backward, Left/ i-Style colour/ ECO/ Blue Light Reducer, Right/ Volume |
| User controls | picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync, motion blur reduction, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB charge, USB C speed), input select, audio settings (volume, mute audio), recall |
| Speakers | 2 x 5W |
| Convenience | Kensington-lock™ prepared, DDC2B |

04 MECHANICAL

| | |
|-------------------------------------|--------------------------|
| Display position adjustments | height, swivel, tilt |
| Height adjustment | 150mm |
| Swivel stand | 90°; 45° left; 45° right |

| | |
|--------------------------------|-----------------|
| Tilt angle | 23° up; 5° down |
| VESA mounting | 100 x 100mm |
| Cable management system | yes |

05 ACCESSORIES INCLUDED

| | |
|---------------|---------------------------------|
| Cables | power, USB, HDMI, DP |
| Other | quick start guide, safety guide |

06 POWER MANAGEMENT

| | |
|--------------------------|---|
| Power supply unit | internal |
| Power supply | AC 100 - 240V, 50/60Hz |
| Power usage | 55W typical, 0.5W stand by, 0.3W off mode |

07 SUSTAINABILITY

| | |
|--|---|
| Regulations | TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| Energy efficiency class (Regulation (EU) 2017/1369) | F |
| EPEAT Silver | *registration varies by country, go to www.epeat.net for details |
| REACH SVHC | above 0.1%: Lead |

08 DIMENSIONS / WEIGHT

| | |
|-------------------------------------|---------------------------|
| Product dimensions W x H x D | 807 x 426 (576) x 245.5mm |
| Box dimensions W x H x D | 940 x 500 x 198mm |
| Weight (without box) | 9.7kg |
| Weight (with box) | 13.8kg |
| EAN code | 4948570125135 |