



# 34" UWQHD curved monitor with USB-C dock, LAN, KVM switch and 15cm height adjustable stand

The XCB3497WQSNP is a 34-inch curved monitor that incorporates a KVM switch and a USB-C dock to simplify your workspace. The KVM switch enhances multitasking by allowing you to control multiple computers from a single monitor, keyboard, and mouse. The USB-C dock reduces cable clutter and simplifies connectivity even further, allowing a single cable to carry video, data, and power to charge your notebook. Additionally, when the monitor is connected to a LAN network, your notebook automatically gains network access. The VA panel technology delivers high contrast and deep black levels and wide viewing angles for consistent image quality regardless of your position for a richer and more vivid viewing experience.

For optimal comfort, the 15cm height-adjustable stand allows you to customize the screen position, while the Flicker-Free panel and Blue Light reduction function help minimize eye strain.



# - USB CAME

#### **KVM SWITCH**

Having a monitor with a KVM switch allows you to share the devices connected via USB to your monitor with two different PCs. Just change the signal input in the OSD menu of the monitor and your keyboard, mouse and webcam will switch from your work laptop to your gaming PC.

#### **USB-C Dock**

The dock allows you to connect your laptop with a single cable to the monitor to both make sure it is charged and connected to a wired network and signal from the laptop is sent to the monitor. With additional USB-ports, your mouse, keyboard or webcam can also be connected to the monitor. All thanks to a single cable connecting your laptop\* to the USB C dock in the monitor.

\*Functions vary depending on your laptop USB-C support.

# 01 DISPLAY CHARACTERISTICS

Diagonal34", 86.7cmPanelVA panel, matte finishCurved1500RNative resolution3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C)Aspect ratio21:9Panel brightness350 cd/m²Static contrast3000:1Advanced contrast80M:1Response time (MPRT)0.4msViewing zonehorizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Curved 1500R  Native resolution 3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C)  Aspect ratio 21:9  Panel brightness 350 cd/m²  Static contrast 3000:1  Advanced contrast 80M:1  Response time (MPRT) 0.4ms
Native resolution3440 x 1440 @120Hz (4.9 megapixel UWQHD, DisplayPort & USB-C)Aspect ratio21:9Panel brightness350 cd/m²Static contrast3000:1Advanced contrast80M:1Response time (MPRT)0.4ms
Aspect ratio         21:9           Panel brightness         350 cd/m²           Static contrast         3000:1           Advanced contrast         80M:1           Response time (MPRT)         0.4ms
Panel brightness 350 cd/m²  Static contrast 3000:1  Advanced contrast 80M:1  Response time (MPRT) 0.4ms
Static contrast 3000:1  Advanced contrast 80M:1  Response time (MPRT) 0.4ms
Advanced contrast 80M:1  Response time (MPRT) 0.4ms
Response time (MPRT) 0.4ms
Viewing zone horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support 16.7mln (sRGB: 99%; NTSC: 93%)
Horizontal Sync 30 - 180kHz
Viewable area W x H 797.2 x 333.7mm, 31.3 x 13.1"
Pixel pitch 0.232mm
Colour matte, black

# 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (1x v.2.0 and 1x v. 1.4, 3440x1440 @100Hz, 2560x1440 @120Hz) DisplayPort x1 (v.1.4, 3440 x 1440@ 120Hz) USB-C x1 (3440 x 1440@ 120Hz, PD 95W)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
USB-C DOCK	x1 (Power delivery 95W, LAN, USB v. 3.2 (Gen 1, 5Gbit))
HDCP	yes
Headphone connector	yes
RJ45 (LAN)	x1

# 03 FEATURES

KVM switch	yes
Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync Premium, HDMI: 2560 x 1440 @48-100Hz, DP / USB-C: 3440 x 1440 @48-120Hz
Extra	i-Style Colour
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Joystick: Power/Menu (Centre), Forward/Signal Select, Backward, Left/i-Style colour/ECO/BlueLight Reducer, Right/Volume
User controls	picture adjust (brightness, contrast, Eco, ACR, OD, AdaptiveSync, motion blur reduction, X-Res technology, black tuner), colour settings (6-axis, i-Style colour, blue light reducer, gamma, RGB range, colour temp.,), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, Mac address, USB charge, USB C speed), KVM (HDMI1, HDMI2, DisplayPort, USB C), input select, audio settings (volume, mute audio), recall
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC2B

# **MECHANICAL**

Display position adjustments	swivel, tilt
Height adjustment	150mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

### 05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI, DP, USB-C
Other	quick start guide, safety guide



#### POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	55W typical, 0.5W stand by, 0.3W off mode



## SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	F
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	above 0.1%: Lead



#### DIMENSIONS / WEIGHT

Product dimensions W x H x D	807 x 426 (576) x 245.5mm
Box dimensions W x H x D	807 x 500 x 198mm
Weight (without box)	9.7kg
Weight (with box)	14.1kg
EAN code	4948570125142

© IIYAMA CORPORATION. ALL RIGHTS RESERVED