

## IFP INTERACTIVE DISPLAYS

## INFORMATION

## 75" 4K UHD Google EDLA Certified IFP Interactive Display – Where Design Meets Performance

Elegance and functionality come together in the ProLite TE7515A-B1AG. This 75" 4K UHD panel not only delivers precision and performance, but also brings a premium look to modern classrooms and collaborative business environments.



With its button-free front panel (only a discreet power button), integrated pen holders, and a stylish fabric-covered bottom bezel that subtly houses high-quality front-facing speakers, the TE7515A elevates the visual experience of any room. It's more than a tool—it's part of your space. A built-in camera enhances remote collaboration and hybrid meetings, ensuring you're always seen clearly without extra hardware. Coupled with PureTouch-IR+ technology and Palm Rejection, it offers fluid and natural writing on the Zero Airgap LCD, eliminating parallax for an intuitive feel.

Powered by iiWare 21E with Android 14 (EDLA Certified), the display integrates effortlessly into Google environments. Features like WiFi 6, Bluetooth 5.0, NFC reader, and PIR motion sensor add a layer of connectivity, energy efficiency, and access control. With [iiControl](#) (DMS), [iiShare](#) and integrated [EShare](#) app (wireless screen sharing), the TE7515A-B1AG promotes seamless teamwork—whether you're presenting, teaching, or brainstorming.

The TE7515A-B1AG isn't just an interactive display—it's a centerpiece for connection, creativity, and collaboration, all wrapped in a refined, modern design.



## Google EDLA Certified

Google Enterprise Device License Agreement allows Google apps, accounts, files, and collaborative tools to be easily accessed directly from the Google EDLA certified iiyama displays, offering seamless integration with the Google ecosystem and the entire Microsoft 365 suite for enhanced user experience, productivity, and collaboration in all environments, especially the education and enterprise sectors alike.



## iiWare 21E (Android 14 OS)

Empower your presentations with iiWare 2a1E, featuring featuring Google EDLA, iiControl (DMS), iiShare (Wireless Presentation), WhiteBoard, Cloud Drives, iiBrowser and file manager via an intuitive and user-friendly software that allows you to effortlessly manage, customize, and access various applications with ease.



## Quick Radial Menu

This feature provides a quick way to operate the interactive display. Long press with five fingers to bring up the Quick Radial Menu. Users can directly select the frequently used apps in the apps menu and place them in the Quick Radial Menu.



## iiControl - DMS

iiControl provides organizations with a convenient and fast unified management solution for terminal equipment, builds an efficient and real-time equipment management system, helps digitize the campus/office estate environment and makes device management ultra convenient. iiyama DMS is committed to maintaining compliance with GDPR.

## SPECIFICATION

### 01 DISPLAY CHARACTERISTICS

Design	Thin bezel
Diagonal	74.5", 189.3cm
Panel	IPS
Touch Glass	Anti-Glare glass with Anti-Gloss treatment, Anti-Bacterial coating, Ultra Smooth writing, Zero Bonding
Panel	IPS
Native resolution	3840 x 2160 (8.3 megapixel 4K UHD)
Aspect ratio	16:9
Panel brightness	550 cd/m <sup>2</sup>
Light transmittance	88%
Static contrast	1200:1
Response time (GTG)	8ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (NTSC 72%)
Viewable area W x H	1650 x 928mm, 65 x 36.5"
Pixel pitch	0.430mm
Bezel colour and finish	black, matte

### 02 TOUCH

Touch technology	DeepContrast-IR+
Touch points	40, 32pt writing (HID, only with supported OS, 32pt Touch with Android)
Touch accuracy	+/- 1mm
Touch method	stylus, finger, glove (Passive pen, Opaque objects)
Touch interface	USB
Supported operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Palm rejection	yes

### 03 INTERFACES / CONNECTORS / CONTROLS

Digital signal input	HDMI x2 (2.0, max. 3840x2160 @60Hz, YUV444, ARC on HDMI #1) DisplayPort x1 (1.2, max. 3840x2160 @60Hz) USB-C x1 (3.2, Gen 1, 5Gbit), 3840x2160 @60Hz (YUV444/ RGB444), DP 1.2 Alt mode, PD 100W, Data, Touch)
Audio input	Mini jack x1 (Microphone)
Monitor control input	RS-232c x1 (DSUB 9pin)
Digital signal output	HDMI x1 (2.0, max. 3840x2160 @60Hz, YUV444 / RGB444) USB-C x1 (3.2, Gen 1, 5Gbit), 3840x2160 @60Hz (YUV444/ RGB444), DP 1.2 Alt mode)

<b>Audio output</b>	S/PDIF (Optical) x1 Mini jack x1 (Headphone) Speakers 2 x 20W (Front facing + 20W Subwoofer on backside)
<b>Monitor control output</b>	OPS Slot x1 (Intel OPS 80pin)
<b>HDCP</b>	2.2
<b>USB ports</b>	x5 (media playback / peripherals / storage – side: 2x 3.2 (Gen 1, 5Gbit), 1x 2.0 (Android only), 1x USB-C IN 3.2 (Gen 1, 5Gbit, 100W PD), 1x USB-C OUT 3.2)
<b>RJ45 (LAN)</b>	x2 (IN / OUT, Auto switch for PC & Android, 1000MB)
<b>Microphone</b>	8-Array (8m voice-pickup)

## 04 FEATURES

<b>Integrated software</b>	iiWare 21E (Android 14 OS) featuring Google EDLA, iiControl (DMS), Whiteboard, iiBrowser, file manager, cloud drives and iiShare, plus EShare for wireless connection with Windows/iOS/Android devices
<b>WiFi</b>	yes (Built-in WiFi-6, Bluetooth 5.0)
<b>Hardware</b>	CPU: RK3576 Octa-core A72*4 + A53*4, GPU: Mali G52 MC3, RAM: 16GB, ROM: 128GB
<b>Extra</b>	Sensors: Ambient light, NFC Reader, PIR Motion, Pen Pick-up; Slot for optional OPS PC, Micro SD card slot, 4x Touch pen (anti-bacterial coating)
<b>Kiosk mode</b>	yes
<b>PiP</b>	yes
<b>Media playback</b>	yes
<b>Glass thickness</b>	3.2mm
<b>Glass hardness</b>	7H
<b>Housing (bezel)</b>	metal
<b>OSD key lock</b>	yes

## 05 GENERAL

<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, CZ, NL, PL, CAT, SV, FI, DA, NB
<b>Control buttons</b>	Power
<b>User controls</b>	general settings (input, volume, backlight), audio (volume, bass, treble, balance, sound mode, mute), screen settings (aspect ratio, pixel shift), display settings (brightness, contrast, hue, sharpness, display mode colour temp), settings (wireless & networks, share, device, personal, system)
<b>Blue light reducer</b>	yes
<b>Flicker free</b>	yes
<b>Plug&amp;Play</b>	DDC2B
<b>Warranty</b>	5 years (for details and eligible countries please check the Warranty section of our website)

## 06 MECHANICAL

<b>Orientation</b>	landscape
<b>Fanless design</b>	yes
<b>VESA mounting</b>	800 x 400mm

<b>Operation temperature range</b>	0°C - 40°C
<b>Storage temperature range</b>	- 20°C - 60°C
<b>MTBF</b>	50.000 hours (excluding backlight)

## 07 ACCESSORIES INCLUDED

<b>Cables</b>	power (EU 3m, UK 3m), USB (3m), HDMI (3m)
<b>Touch pen</b>	x4 (Dual function tips, anti-bacterial coating)
<b>Guides</b>	quick start guide, safety guide
<b>Other</b>	Wall Mounting Bracket (VESA 800x400), Webcam Mounting Bracket, Cable ties (6pcs)
<b>Remote control</b>	yes (batteries included)

## 08 POWER MANAGEMENT

<b>Power supply unit</b>	internal
<b>Power supply</b>	AC 100 - 240V, 50/60Hz
<b>Power usage</b>	216W typical, 0.5W stand by, 0.3W off mode

## 09 SUSTAINABILITY

<b>Regulations</b>	CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, EPEAT, REACH (RoHS)
<b>Energy efficiency class (Regulation (EU) 2017/1369)</b>	G
<b>EPEAT</b>	EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Bronze certification means the monitor meets all required criteria. EPEAT Bronze is valid in countries where iiyama registers the product. Please visit <a href="http://www.epeat.net">www.epeat.net</a> for the registration status in your country.
<b>REACH SVHC</b>	above 0.1%: Lead

## 10 DIMENSIONS / WEIGHT

<b>Product dimensions W x H x D</b>	1710.2 x 1036.3 x 87.1mm
<b>Box dimensions W x H x D</b>	1860 x 1125 x 185mm
<b>Weight (without box)</b>	54.6kg
<b>Weight (with box)</b>	67.6kg
<b>EAN code</b>	4948570124855

## 11 COMPATIBLE ACCESSORIES

<b>Other</b>	MD-CAR2031-B1, MD-WLIFT2031-W1, UC-CAM10PRO-1, UC CAM120ULB-1, OPC51204BC-1, WP-D003C
--------------	---



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © **Iiyama CORPORATION. ALL RIGHTS RESERVED**