





# Join the pro squad with the 27" G-Master Red Eagle, built for pure speed with a 240Hz refresh rate.

Gain the competitive edge you need to unlock your full gaming potential with the 27" GB2771HSU monitor with FHD (1920x1080) resolution. Featuring an ultra-fast 0.4ms MPRT and a 240Hz refresh rate, this monitor ensures smooth gameplay. Compatible with NVIDIA G-SYNC so you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas and the IPS panel technology guarantees superb image quality.

Available also with fixed stand :  $\underline{G-Master\ G2771HSU-B1\ (1920x1080)}$ ,  $\underline{G-Master\ G2771HS-B1\ (1920x1080)}$  and  $\underline{G-Master\ G2771QS-B1\ (2560x1440)}$ 



Fast IPS

The lightning-fast IPS panel with Full HD 1920x1080 resolution delivers ultra-smooth gameplay and vibrant, true-to-life colours with exceptional accuracy and wide viewing angles.



240Hz

With 240Hz refresh rate the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.

# DISPLAY CHARACTERISTICS

Diagonal	27", 68.6cm
Panel	Fast IPS, haze 25%
Native resolution	1920 x 1080 @240Hz (2.1 megapixel full HD, DisplayPort)
Aspect ratio	16:9
Panel brightness	350 cd/m <sup>2</sup>
Static contrast	1000:1
Advanced contrast	80M:1
Response time (MPRT)	0.4ms
Viewing zone	horizontal/vertical: horizontal°/vertical 178°, right/left: 0°/0°, up/down: 0°/0°
Colour support	16.7mln 8bit
Horizontal Sync	30 - 285kHz
Viewable area W x H	597,9 x 336.3mm, 23.5 x 13.2"
Pixel pitch	0.311mm
Colour	matte, black

### 02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0, max. 1920 x 1080 @240Hz) DisplayPort x1 (v.1.2, max. 1920 x 1080 @240Hz)
USB HUB	x2 (1x Type A v.3.2 Gen 1 (5Gbps, 4.5W), 1x Type C (5Gbps, 5W))
HDCP	yes
Headphone connector	yes



Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	G-SYNC - 1920 x 1080 @48-240Hz, DisplayPort Only
Extra	i-Style Colour
HDR	Yes, HDR10 Ready
OSD languages	EN, DE, FR, IT, PT, RU, JP, CZ, NL, PL
Control buttons	power switch, joystick, menu (center), up / signal select, down / shortcut, left / volume -, right / volume + $$
User controls	picture adjust (contrast, brightness, OverDrive, HDR, Adaptive Sync, Adv. Contrast, night mode, blue light reducer, Motion Blur Reducer, gamma), input select (input source), audio adjust (volume, mute), store user setting (user modes), colour settings (6-axis, colour temperature, user preset, black tuner), image adjust (i-Style colour, X-Res Technology, sharpness, HDMI range, Direct Drive Mode, video mode adjust), language, setup menu (OSD H. position, OSD V. position, OSD time, opening logo, power LED, DDC/CI control, USB charge), display information, reset (reset all)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX



### MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	90°; 45° left; 45° right

Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

# 05 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.8m), HDMI (1.8m), DP (1.8m)
Other	quick start guide, safety guide

# 06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC AC - 100V, 240 /V, 50Hz
Power usage	19W typical, 0.5W stand by, 0.3W off mode

# 07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	E
REACH SVHC	above 0.1%: Lead

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	612 x 408.5 (553.5) x 213mm
Box dimensions W x H x D	690 x 140 x 465mm
Weight (without box)	5.6kg
Weight (without stand)	3.8kg
Weight (with box)	8.2kg
EAN code	4948570126439



© IIYAMA CORPORATION. ALL RIGHTS RESERVED