




Get ahead with the 24" GB2441HSU Black Hawk monitor with IPS Panel Technology, 1ms MPRT and height adjustable stand

Indulge in exceptional gaming excellence with the 24" GB2441HSU monitor. This display boasts cutting-edge IPS panel technology, a 144Hz refresh rate, and an ultra-swift 1ms MPRT response time. Elevate your gaming adventure to the next level, thanks to FreeSync Technology and the Black Tuner function, ensuring crystal-clear visibility even in the darkest scenes. In addition, equipped with a height adjustable stand (15cm).

Available also with fixed stand : [G-Master G2441HSU-B1](#)



144Hz

Rapid refresh rate and frame rate guarantee smooth, blur free and judder free graphics, with lower latency and lag improving response times for fast paced games. Especially suited to the fast pace games like FPS, racers, MOBA and sports where the 144Hz refresh rate delivers the crisp and sharp images needed to raise your game.



1ms

Fast response time is key to ultra-smooth gaming. It reduces ghosting and blurring providing the user with an improved graphic performance.

01 DISPLAY CHARACTERISTICS

Diagonal	23.8", 60.5cm
Panel	IPS, matte finish
Native resolution	1920 x 1080 @144Hz
Aspect ratio	16:9
Panel brightness	350 cd/m ²
Static contrast	1500:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn
Horizontal Sync	30 - 163kHz
Viewable area W x H	527 x 296.5mm, 20.7 x 11.7"
Pixel pitch	0.2745mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 (v.1.4) DisplayPort x1 (v.1.2)
USB HUB	x2 (v.2.0 DC5V, 500mA)
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	FreeSync - 1920 x 1080 @48-144Hz
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Joystick / Power Button: Power / Menu (Center), Up / Input Select, Down, Right / Volume / Mute Audio, Left / Brightness / Adaptive Sync / Night Mode / Motion Blur Reduction / i-Style Colour / ECO
User controls	picture adjust (contrast, brightness, OD, Adaptive Sync, Adv. Contrast, Night Mode, Motion Blur Reduction, Gamma), input select (Auto/Manual, HDMI, DP), audio settings (volume, mute audio), store user settings (user modes), colour settings (6-Axis, colour temperature, user preset, i-style colour, blue light reducer, black tuner), image adjust (sharpness, RGB range, video mode adjust, x-res technology), language, setup menu (OSD h. position, OSD v. position, OSD time, OSD background, OSD rotate, opening logo, power LED, ddc/ci control), display information, reset (reset all)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, pivot (rotation), swivel, tilt
Height adjustment	150mm
Rotation (PIVOT function)	90°
Swivel stand	45°; 45° left; 45° right
Tilt angle	23° up; 5° down

VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.5m), USB (1.5m), HDMI (1.5m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	12W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	C
REACH SVHC	above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	539 x 351 (501) x 390mm
Box dimensions W x H x D	685 x 395 x 126mm
Weight (without box)	4.6kg
Weight (with box)	5.9kg
EAN code	4948570126323



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED